

iiyama ProLite T1633MSC-B1 computer monitor 39.6 cm (15.6") 1920 x 1080 pixels Full HD LCD Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1633MSC-B1** · EAN: **4948570122523** · Prekės kodas: **707138**



433,91 €

Kaina su PVM

Be PVM: **358,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ projective capacitive
- ✓ DisplayPort x1
- ✓ HDMI x1



Aprašymas

The ProLite T1633MSC-B1 uses projective capacitive touch technology, built into an eye catching bezel with edge-to-edge glass. The screen guarantees high durability, scratch-resistance, clarity and a perfect picture performance. Featuring IPS Panel Technology and Full HD (1920x1080) resolution, it offers natural, highly accurate colours and wide viewing angles. The flexible stand can be positioned at several angels creating a comfortable and ergonomic user experience and the integrated cable management system hides all the cables and electrical wires giving a neat and cable-free workspace. In addition to the superb image quality, the screen comes with an IP54 rating, which means the screen and bezel is dust and water resistant from the front. A perfect solution for retail applications.

Techninė specifikacija

Specifications

Sandėlio grupė

> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]

Display

Display diagonal	39.6 cm (15.6")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Display brightness (typical)	450 cd/m²
Display brightness	385 cd/m²
Response time measurement type	GTG (Gray to Gray)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.179 x 0.179 mm
Horizontal scan range	30 - 68 kHz
Viewable size, horizontal	34.4 cm
Viewable size, vertical	19.4 cm
Display diagonal (metric)	39.5 cm

Performance

NVIDIA G-SYNC	No
AMD FreeSync	No
Low Blue Light technology	Yes
Palm rejection	Yes

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W

Design

Market positioning	Home
Product colour	Black
Front bezel colour	Black

Ports & interfaces

Built-in USB hub	Yes
HDMI	Yes
USB hub version	2
Number of downstream ports	2
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	No
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	90 - 5°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Number of OSD languages	12

Power

Energy efficiency class (SDR)	C
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	7.7 kWh
Power consumption (typical)	12 W
Power consumption (standby)	8 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

AC adapter output voltage	12 V
Power supply type	External
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	389 mm
Depth (with stand)	200 mm
Height (with stand)	284 mm
Weight (with stand)	3.4 kg
Weight (without stand)	5.3 kg
Packaging data	
Package width	475 mm
Package depth	169 mm
Package height	343 mm
Package weight	5.3 kg
Package type	Box
Packaging content	
Cables included	AC, USB, HDMI
Power adapter included	Yes
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
AC adapter included	Yes
Brightness	385 cd/m²
Packaging content	AC adapter
Active display area (W x H)	344.2 x 193.6 mm
USB ports quantity	2
Weight	3.4 kg
Height	284 mm
Width	389 mm
Depth	200 mm

Compliance certificates	CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Certification	CE, TÜV-Bauart, EAC, RoHS, ErP, WEEE, REACH, UKCA
User controls	Luminance (contrast, brightness, i-Style color, adv. contrast, overdrive), image setup (aspect ratio), color temp., OSD setup (H. position, V. position, timeout, language, touch wake up), extra (input select, DDC/CI, reset, opening logo, LED, volume, information)
Touch method	stylus, finger, glove (latex)
Control panel	Power, Menu, Volume +, Volume -, Input
Technical details	
Native refresh rate	60 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	48,00cm × 35,00cm × 17,00cm
Svoris	5,34kg