

iiyama ProLite T1932MSC-B2S computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1932MSC-B2S** · EAN: **4948570127771** · Prekės kodas: **707444**



551,91 €

Kaina su PVM

Be PVM: **456,12 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48.3 cm (19") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 75 Hz Response time: 14 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1280 x 1024 pixels SXGA Panel type: IPS
- ✓ Energy efficiency class (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, WEEE



Aprašymas

Built for intuitive interaction, the ProLite T1932MSC-B2S touchscreen monitor combines precise touch response, durable glass protection and clear image quality in one practical display. Whether used for customer-facing applications, point-of-sale systems, information desks or everyday professional work, it offers a smooth and natural touch experience that feels familiar from the first use. The screen delivers sharp, colourful visuals with wide viewing angles thanks to its IPS panel technology. Its tough scratch-resistant glass surface and front-facing IP54 protection against dust and water splashes make it suitable for frequent use, helping the display stay reliable in demanding, even industrial environments. A stable, adjustable stand allows flexible positioning, making the monitor easy to adapt to different users and setups. Finished with a sleek edge-to-edge glass design, it brings a modern, professional appearance to any interactive workspace.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
HD type	SXGA
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	250 cd/m²
Display brightness	225 cd/m²
Response time measurement type	GTG (Gray to Gray)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.293 x 0.293 mm
Horizontal scan range	31 - 80 kHz
Vertical scan range	50 - 75 Hz
Viewable size, horizontal	37.5 cm
Viewable size, vertical	30 cm
Display diagonal (metric)	48 cm
DDC/CI	Yes
Performance	
Component video sync	Separate Sync
Multimedia	

Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	2 W
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	13 kWh
Power consumption (typical)	20 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V

AC input frequency	50/60 Hz
Input current	1 A
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	432 mm
Depth (with stand)	239.5 mm
Height (with stand)	413.5 mm
Weight (with stand)	5.4 kg
Packaging data	
Package width	530 mm
Package depth	190 mm
Package height	495 mm
Package weight	7.4 kg
Package type	Box
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort, Audio
Quick start guide	Yes
Audio cable length	1.8 m
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.

Brightness	225 cd/m ²
Packaging content	Screwdriver
Active display area (W x H)	375 x 300 mm
Weight	5.4 kg
Height	413.5 mm
Width	432 mm
Depth	239.5 mm
Compliance certificates	CE, cULus, EAC, REACH, RoHS, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
User controls	Picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (timeout, position, H-position, V-position), option (reset, language, source select, display mode, volume, factory)
Touch method	stylus, finger, glove
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power
Matmenys ir svoris	
Matmenys (I × P × A)	53,00cm × 49,00cm × 20,00cm
Svoris	7,21kg