

EIZO FlexScan EV3851X-WT computer monitor 95.2 cm (37.5") 3840 x 1600 pixels UltraWide Quad HD+ LCD White

Gamintojas: **EIZO** · Modelis: **EV3851X-WT** · EAN: **4995047072201** · Prekės kodas: **708021**



1 849,90 €

Kaina su PVM

Be PVM: **1 528,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 37.5-inch ultrawide monitor in 24:10 aspect ratio with 3840 x 1600 pixels (111 ppi) for excellent readability
- ✓ Large curved display with a narrow bezel and ultra-sleek design
- ✓ Contrast ratio 1000:1, brightness 300 cd/m², 178° viewing angle
- ✓ Display P3, DCI-P3, and BT.709 color presets for Apple devices and video production
- ✓ USB-C port with docking function for video signal, USB, LAN, and power delivery up to 94 watts
- ✓ Signal inputs: USB-C (DisplayPort Alt Mode), DisplayPort, two HDMI
- ✓ Auto EcoView, EcoView Index, and EcoView Optimizer for maximum energy savings and optimal ergonomics
- ✓ KVM switch and picture-by-picture for two computers
- ✓ Proven to be produced in an environmentally conscious and socially responsible manner
- ✓ 7-year warranty for maximum investment security



Aprašymas

With a 37.5-inch screen size, curved display, and UWQHD+ resolution (3840 x 1600), the EV3851X is ideal for organizing large amounts of data and working with multiple applications without the distracting bezels of a multi-monitor setup. It comes with a 7-year manufacturer's warranty thanks to high-quality design, meticulous manufacturing, and strict quality control in Japan. With its USB-C port, video, audio, LAN, data, and 94 watts of power can be transmitted to a laptop via a single cable—convenient for home offices and hot-desking. HDMI and DisplayPort interfaces round out the connectivity options. Thanks to the integrated KVM switch, two PCs can be connected simultaneously, operated with a single set of mouse and

keyboard, and even displayed at the same time using picture-by-picture. Various display modes support common color standards such as Display P3 (used in Apple devices), DCI-P3, and BT.709, making them suitable for video editing and previewing; Switching between them is easy with the push of a button. The monitor meets international sustainability standards such as ENERGY STAR®, TCO Certified Generation 10, EPEAT, and EPEAT Climate+ to support Environmental, Social, and Governance (ESG) goals as well as SDG (Sustainable Development Goals).

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	95.2 cm (37.5")
Display resolution	3840 x 1600 pixels
Native aspect ratio	24:10
Display technology	LCD
Touchscreen	No
HD type	UltraWide Quad HD+
Panel type	IPS
Response time	5 ms
Screen shape	Curved
Contrast ratio (typical)	2000:1
Maximum refresh rate	60 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	300 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Screen curvature rating	2300R
Supported graphics resolutions	3840 x 1600, 3440 x 1440, 2560 x 1600 (WQXGA), 2560 x 1440, 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 1680 x 1050 (WSXGA+), 1600 x 1200 (UXGA), 1280 x 1024 (SXGA), 1024 x 768 (XGA), 800 x 600 (SVGA), 720 x 400, 640 x 480 (VGA)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.229 x 0.229 mm
Pixel density	111 ppi
Viewable size, horizontal	88 cm
Viewable size, vertical	36.6 cm
Digital horizontal frequency	31 - 99 kHz

Digital vertical frequency	29 - 61 Hz
Display diagonal (metric)	95 cm
Colour gamut standard	sRGB, DCI-P3
DCI-P3 coverage	95%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Office
Product colour	White
Feet colour	White
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C, USB Type-B
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	94 W
HDMI ports quantity	2
DisplayPorts quantity	1

Headphone outputs	1
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes
HDCP	Yes
HDCP version	1.4/2.3
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	19.5 cm
Swivelling	Yes
Swivel angle range	-70 - 70°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, French, Spanish, Italian, Swedish
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	26 kWh
Power consumption (typical)	26 W
Power consumption (standby)	0.3 W
Power consumption (max)	220 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%

Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	893.9 mm
Depth (with stand)	247.1 mm
Height (with stand)	416.9 mm
Weight (with stand)	13 kg
Width (without stand)	893.9 mm
Depth (without stand)	112.3 mm
Height (without stand)	402.2 mm
Weight (without stand)	10.3 kg
Packaging content	
Stand included	Yes
Cables included	USB Type-C to USB Type-C, USB Type-A to USB Type-B, DisplayPort, Power
Quick start guide	Yes
Sustainability	
Sustainability certificates	EPEAT Gold, EPEAT Climate +, TCO, ENERGY STAR
Sustainability compliance	Yes
Other features	
Picture-by-Picture (PbP)	Yes
Automatic brightness control	Yes
Warranty period	7 year(s)
Look-up table (LUT) bit depth	14
Compliance certificates	CE, UKCA, TÜV mark, Federal Communications Commission (FCC), RoHS, PTCRB, CCC, WEEE, VCCI, PSE, ICES
Ethernet LAN data rates	2500 Mbit/s
Ethernet LAN (RJ-45) ports	1
Certification	CE, UKCA, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified generation 10, TÜV/Low Blue Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCCB, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, EPEAT EPEAT 2018 Gold (US), EPEAT Climate+
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	25,00cm × 89,00cm × 61,00cm
Svoris	19,70kg