

EIZO ColorEdge CS2400R computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black

Gamintojas: **EIZO** · Modelis: **CS2400R** · EAN: **4995047065104** · Prekės kodas: **708246**



651,90 €

Kaina su PVM

Be PVM: **538,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24" IPS LCD with 1920 x 1200 pixels, 16:10 format
- ✓ 100 % colour space coverage of sRGB and Rec 709
- ✓ 300 cd/m² maximum brightness, contrast 1000:1
- ✓ 10-bit display, 16-bit look-up table
- ✓ Exact hardware calibration of brightness, white point and gamma
- ✓ Digital Uniformity Equalizer for perfect luminance distribution and colour purity
- ✓ USB-C (DisplayPort signal and up to 70 Watt Power Delivery), DisplayPort and HDMI input
- ✓ USB hub with two 5Gbps (USB 3.x) and two USB 2 downstream



Aprašymas

The ColorEdge CS2400R is the most affordable entry into the world of maximum precision: the panel offers full coverage of the sRGB and Rec 709 colour spaces. The Digital Uniformity Equalizer (DUE) ensures homogeneous image representation and the 16-bit look-up table guarantees absolutely precise colour representation with up to 10 bits. On the one hand, the exact factory calibration guarantees the highest precision "out of the box". On the other hand, the regularly recommended recalibration is done in no time at all. This means that photographers, filmmakers or image editors can always rely on their monitor to show them an absolutely precise view of their image file. The docking functions via USB-C allow the image signal to be transferred and the monitor's USB hub to be powered with just one cable. In addition, a mobile device can be supplied with up to 70 watts of charging current. In this way, the CS2400S becomes the central dock of the creative workflow with a flick of the wrist. Alternatively, the

monitor can of course also be operated via HDMI or DisplayPort as well as USB-B upstream.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	61.2 cm (24.1")
Display resolution	1920 x 1200 pixels
Native aspect ratio	16:10
Display technology	LCD
Touchscreen	No
HD type	WUXGA
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	60 Hz
Display number of colours	1.07 billion colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	300 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	1920 x 1200 (WUXGA), 1920 x 1080 (HD 1080)
Supported video modes	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.27 x 0.27 mm
Pixel density	94 ppi
Horizontal scan range	15 - 76 kHz
Vertical scan range	23 - 61 Hz
Viewable size, horizontal	51.8 cm
Viewable size, vertical	32.4 cm
Display diagonal (metric)	61.1 cm
Colour depth	10 bit
Colour gamut standard	sRGB

sRGB coverage (typical)	100%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Photo editing
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	70 W
HDMI ports quantity	1
DisplayPorts quantity	1
Built-in KVM switch	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington

Adjustable height (max)	15.5 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	0 - 344°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Number of OSD languages	6
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	19 kWh
Power consumption (typical)	15 W
Power consumption (standby)	0.3 W
Power consumption (max)	134 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	554 mm
Depth (with stand)	245 mm
Height (with stand)	396 mm
Weight (with stand)	8.1 kg
Width (without stand)	554 mm
Depth (without stand)	64 mm

Height (without stand)	362 mm
Weight (without stand)	5.1 kg
Packaging content	
Stand included	Yes
Cables included	AC, HDMI, USB Type-A to USB Type-B, USB Type-C to USB Type-C
Quick start guide	Yes
Other features	
Hardware calibration	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	16
Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, RoHS, WEEE, China RoHS, CCC
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	66,00cm × 52,00cm × 33,00cm
Svoris	11,96kg