

iiyama ProLite TF1734MC-B8X kompiuterio monitorius 43,2 cm (17") 1280 x 1024 pikseliai SXGA LCD Lietimui jautrus ekranas Ant stalo Juoda

Gamintojas: **IIYAMA** · Modelis: **TF1734MC-B8X** · EAN: **4948570127818** · Prekės kodas: **708566**



519,90 €

Kaina su PVM

Be PVM: **429,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 43,2 cm (17") Juoda
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas forma: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 75 Hz Reakcijos laikas: 5 ms
- ✓ 1280 x 1024 pikseliai SXGA Skydo tipas: TN
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, WEEE



Aprašymas

17" Open Frame touchscreen monitor with edge-to-edge glass and Touch Through-Glass function for flexible integration

The ProLite TF1734MC-B8X is a 17" Open Frame touchscreen monitor designed for integration into kiosks, retail systems, interactive displays and custom installations. Its 10-point PCAP touch technology provides accurate multi-touch operation, while the edge-to-edge glass surface offers durability, scratch resistance and a clean, professional appearance.

With IP65-rated front protection, the screen is resistant to dust and splashing water from the front, making it suitable for demanding public and commercial environments. The anti-fingerprint coating helps keep the display clear and easy to use, even with frequent interaction.

For applications requiring additional protection, the Touch Through-Glass function allows reliable touch operation through a glass overlay up to 6 mm. The monitor can be installed in landscape, portrait or face-up orientation, while optional Open Frame mounting brackets support easy and secure integration into different installation designs. For ease of integration, the monitor can be equipped with optional external mounting brackets (OMK1-1).

Techninė specifikacija

Display	
Display diagonal	43.2 cm (17")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LCD
Touchscreen	Yes
HD type	SXGA
Panel type	TN
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display number of colours	16.7 million colours
Touchscreen type	Table
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (peak)	350 cd/m²
Display brightness (typical)	300 cd/m²
Display brightness	300 cd/m²
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
Pixel pitch	0.264 x 0.264 mm
Horizontal scan range	31 - 80 kHz
Viewable size, horizontal	33.8 cm

Viewable size, vertical	27 cm
Display diagonal (metric)	43 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Palm rejection	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Glass thickness	3 mm
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
Headphone out	No
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Ergonomics	
VESA mounting	Yes
Cable lock slot	No
Height adjustment	No
Panel mounting interface	100 x 100 mm
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Power consumption (typical)	13 W
Power consumption (standby)	1.5 W

Power consumption (off)	0.3 W
AC adapter output voltage	12 V
Power supply type	External
Weight & dimensions	
Width (with stand)	369 mm
Depth (with stand)	47.5 mm
Height (with stand)	307 mm
Weight (with stand)	3.6 kg
Packaging data	
Package width	387 mm
Package depth	455 mm
Package height	145 mm
Package weight	5.2 kg
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP65
Positional accuracy	2 mm
AC adapter included	Yes
Brightness	300 cd/m²
Packaging content	AC adapter
Active display area (W x H)	338 x 270 mm
Weight	3.6 kg
Height	307 mm
Width	369 mm
Depth	47.5 mm
Compliance certificates	CE, cULus, EAC, REACH, RoHS, UKCA, WEEE

User controls	picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (time out, position, H-position, V-position, Touch switch), option (reset, language, source select, display mode, factory)
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select, Power

Technical details

Native refresh rate	75 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	46,00cm × 39,00cm × 14,00cm
Svoris	5,48kg

Energijos efektyvumas ir ekologinis projektavimas



11 kWh/1000h



2026/01/01

Energijos efektyvumo klasė

E A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt