

iiyama ProLite T1732MSC-B5X computer monitor 43.2 cm (17") 1280 x 1024 pixels SXGA LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1732MSC-B5X** · EAN: **4948570116041** · Prekės kodas: **709944**



374,89 €

Kaina su PVM

Be PVM: **309,83 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 43.2 cm (17") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Response time: 5 ms
- ✓ 1280 x 1024 pixels SXGA
- ✓ Energy efficiency class (SDR): E



Aprašymas

The ProLite T1732MSC-B5X 17" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours. Available in black and white.

Touch technology - Capacitive

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical

characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and stylus-pen.

ip54

The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

Scratch resistance

Scratch resistance is essential for touch solutions used in public places and schools. This is achieved thanks to a glass overlay covering the screen. It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

Speakers

This LED monitor is equipped with two high quality stereo speakers.

VESA

VESA mount compliance means you can easily mount the LFD to any mounting that complies with the VESA standard.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	43.2 cm (17")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
HD type	SXGA
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.78 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Display brightness	225 cd/m²
Supported graphics resolutions	1280 x 1024 (SXGA)
Aspect ratio	5:4
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
Pixel pitch	0.264 x 0.264 mm

Horizontal scan range	31.4 - 80 kHz
Vertical scan range	56 - 75 Hz
Viewable size, horizontal	33.8 cm
Viewable size, vertical	27.1 cm
Display diagonal (metric)	43 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Number of simultaneous touchpoints (Windows 7)	10
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	2 W
Megapixel (approx.)	1.3 MP
Design	
Product colour	Black
Ports & interfaces	
HDMI	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	12 kWh

Power consumption (typical)	25 W
Power consumption (standby)	2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	387 mm
Depth (with stand)	202 mm
Height (with stand)	342 mm
Weight (with stand)	5.6 kg
Width (without stand)	387 mm
Depth (without stand)	54.5 mm
Height (without stand)	320 mm
Packaging content	
Cables included	DisplayPort, HDMI, USB
Other features	
International Protection (IP) code	IP54
Certification	CB, CE, TÜV-Bauart, VCCI, GOST
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	7,04kg