

iiyama ProLite T1732MSC-B5AG computer monitor 43.2 cm (17") 1280 x 1024 pixels LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1732MSC-B5AG** · EAN: **4948570116065** · Prekės kodas: **712186**



323,90 €

Kaina su PVM

Be PVM: **267,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 43.2 cm (17") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 75 Hz Response time: 5 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1280 x 1024 pixels Panel type: TN
- ✓ Energy efficiency class (SDR): E ErP CB, CE, cULus, REACH, RoHS, VCCI, WEEE



Aprašymas

The ProLite T1732MSC-B5AG 17" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The anti-glare coating helps to avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the touchscreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the touchscreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours. Available in black and white.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Monitore > Monitore (TFT, LCD, LED) [+1779][-139]
Display	
Display diagonal	43.2 cm (17")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
Panel type	TN
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	250 cd/m²
Display brightness	215 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Supported graphics resolutions	1280 x 1024 (SXGA)
Aspect ratio	5:4
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
Pixel pitch	0.264 x 0.264 mm
Horizontal scan range	31.4 - 60 kHz
Vertical scan range	50 - 75 Hz
Viewable size, horizontal	33.8 cm
Viewable size, vertical	27.1 cm
Display diagonal (metric)	43 cm
Performance	
NVIDIA G-SYNC	No

AMD FreeSync	No
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Number of simultaneous touchpoints (Windows 7)	10
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	2 W
Megapixel (approx.)	1.3 MP
Design	
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	12 kWh

Power consumption (typical)	20 W
Power consumption (standby)	1 W
Power consumption (off)	1 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	387 mm
Depth (with stand)	202 mm
Height (with stand)	342 mm
Weight (with stand)	5.6 kg
Width (without stand)	387 mm
Depth (without stand)	54.5 mm
Height (without stand)	320 mm
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort, Audio
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Display viewable area (HxV)	338 x 270.5 mm
Brightness	215 cd/m ²
Packaging content	Touch Panel Driver Disk (CD-ROM)
Active display area (W x H)	338 x 270.5 mm
Weight	5.6 kg
Height	342 mm
Width	387 mm
Depth	202 mm
Compliance certificates	CB, CE, cULus, REACH, RoHS, VCCI, WEEE

User controls	contrast, brightness, auto adjust, H.position, V.position, H.size, fine, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	6,96kg