

NET CAMERA 4MP IR EYEBALL/HDW1439V-A-IL-0280B-S7 DAHUA

 Gamintojas: **DAHUA** · Modelis: **IPC-HDW1439V-A-IL-0280B-S7** · EAN: **6937552445314** · Prekės kodas: **712689**


124,90 €

Kaina su PVM

 Be PVM: **103,22 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the white light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the white light is off and the IR illuminator is on, which reduces light pollution efficiently.

Human Detection

Dahua intelligent algorithms extract moving human targets from videos and filters out alarms that are triggered by non-human targets to increase the accuracy and effectiveness of alarms.

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

WDR

With advanced Wide Dynamic Range (WDR) technology, Dahua network camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

Cyber Security

Dahua network cameras employ a series of security technologies, including security authentication and authorization, access control protocols, trusted protection, encrypted transmission and encrypted storage. These technologies improve the camera's defense against external cyber threats and prevent malicious programs from compromising the device.

Protection (IP67, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normally after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

- 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2560 × 1440)@25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED and warm light, the max. IR illumination distance is 30 m and warm light distance is 30 m
- WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ROI, SMART H.264 +/-H.265+, flexible coding, applicable to various bandwidth and storage environments
- Abnormality detection: Motion detection, video tampering, audio detection, network disconnection, IP conflict and illegal access
- Built in Mic
- 12 VDC/PoE power supply,easy for installation
- IP67 protection

Summary: Dahua Technology Entry IPC-HDW1439V-A-IL-0280B-S7. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0006 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 94°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Detect distance: 64 m, Observe distance: 25.6 m, Recognize distance: 12.8 m | Vendor Homepage: <https://www.dahuasecurity.com/bd/products/All-Products/Dedicated-Products/Project-Exclusive/Network-Cameras/DH-IPC-HDW1439V-A-IL> | Form factor: Turret | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Dynamic range: 120 | Smart search function: Yes | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.0006 | Rotating: Yes | Angle of rotation: 360 | Lens viewing angle, horizontal: 94 | Lens viewing angle, vertical: 52 | Lens viewing angle, diagonal: 111 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Number of Privacy masking areas: 4 | Optical sensor size: 1/2.9 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 64 | Observe distance: 25.6 | Recognize distance: 12.8 | Identify distance: 6.4 | Maximum aperture number: 1.6 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 30 | LED type: IR | Number of illumination LEDs: 2 | Maximum resolution: 2560 x 1440 | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Frame rate: 30 | Video streaming: Yes | Image rotation angles: 180 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR),Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, ICMP, IGMP, P2P | Wi-Fi: No | Bluetooth: No | Number of users: 6 | Streaming method: Multicast | Built-in HDD: No | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Active tampering alarm: Yes | Digital watermark: Yes | HTTPS encryption: Yes | Intelligent Video Surveillance (IVS) system features: Human detection | Mirror: Yes | Video motion detection: Yes | Management software: Smart PSS Lite, DSS, DMSS | Power source type: DC,PoE | Power consumption (typical): 2 | Power consumption (max): 4.6 | Power consumption (Power over Ethernet (PoE)): 2.9 | Power consumption (Power over Ethernet (PoE)) (max): 5.7 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Height: 100.9 | Diameter: 109.9 | Weight: 330 | Compliance certificates: CE | Package weight: 450 | Number of cameras: 1 | Manual: Yes | Browser supported: IE, Chrome, Firefox | Unit Calculated Weight: 0.45 | Product Net Weight: 0.33 | Unit Calculated Volume: 0.00165 | Name: NET CAMERA 4MP IR EYEBALL/HDW1439V-A-IL-0280B-S7 DAHUA

Techninė specifikacija

Specifications

Sandėlio grupė

Network Cameras [+147][-359]