

CyberPower PR2200ELCDSL uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 9 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR2200ELCDSL** · EAN: **4712364146350** · Prekės kodas: **715049**



744,90 €

Kaina su PVM

Be PVM: **615,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 2.2 kVA 1980 W
- ✓ Waveform: Sine
- ✓ 9 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA) 12 V 9 Ah
- ✓ Tower Black



Aprašymas

The Professional Tower Series UPS provides advanced level of power protection to servers, telecom equipment, VOIP, internet working hardware and other mission-critical applications. Featuring Pure Sinewave output and Automatic Voltage Regulation (AVR) stabilizing the AC signal and maintaining a safe voltage, it allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunction LCD readout provides immediate access to precise information of critical power/battery condition and to help users control and manage the machine easily.

The optional SNMP/HTTP Remote Management Capability enables remote management and control of the system through standard web browser. Together with the included PowerPanel Business Edition management software, it could provide corporate servers and critical workstations comprehensive network power management including unattended-shutdown, event logging, reporting, and notifications.

Techninė specifikacija

Specifications	
Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
Features	
UPS topology	Line-Interactive
Output power capacity	2.2 kVA
Output power	1980 W
Waveform	Sine
Input operation voltage (min)	160 V
Input operation voltage (max)	283 V
Input frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Response time	4 ms
Number of input phases	1
Number of output phases	1
Emergency Power Off (EPO)	Yes
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Web-based management	Yes
Management protocols	SNMP, HTTP
Auto-restart	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
USB 2.0 ports quantity	1
Serial ports quantity	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 Ah
Battery voltage	12 V

Number of batteries supported	4
Typical backup time at full load	3 min
Typical backup time at half load	12 min
Battery recharge time	8 h
Automatic battery test	Yes

Design

Form factor	Tower
Product colour	Black
Display type	LCD
LED indicators	Yes

Weight & dimensions

Width	170 mm
Depth	432 mm
Height	221 mm
Weight	23.3 kg

Packaging data

Bundled software	PowerPanel Business Edition
------------------	-----------------------------

Other features

Output connections	8 x IEC 320 C13, 1 x IEC 320 C19
Nominal output voltage	230 V
Nominal input voltage	230 V
Suitable for use in country/location	Europe

Matmenys ir svoris

Matmenys (I x P x A)	58,00cm x 31,00cm x 36,00cm
Svoris	26,70kg