

CyberPower UT650EG-FR uninterruptible power supply (UPS) Line-Interactive 0.65 kVA 360 W 3 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **UT650EG-FR** · EAN: **4712856273281** · Prekės kodas: **715185**



64,90 €

Kaina su PVM

Be PVM: **53,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Energy Saving Technology
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Generator Compatible
- ✓ LED Status Indicator
- ✓ Overload Protection
- ✓ Surge and Spike Protection
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ High-Speed Ethernet Data Transmission
- ✓ EMI and RFI Filtration
- ✓ Configurable Alarm



Aprašymas

CyberPower UT650EG-FR guarantees power protection for IT equipment such as computers, NAS, and storage devices. The product adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The patented GreenPower UPS™ Bypass design achieves ultra-low power consumption to reduce energy costs, and allows a lower operation temperature which extends battery lifespan.

The LED indicator shows the utility, battery and operating status of the UPS. It is also compatible with generators to extend power continuity. Other features include overload protection, EMI filter and configurable alarm to safeguard your devices. Its tower design allows users to place it easily on desks or other tight spaces.

Techninė specifikacija

Specifications	
Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
Features	
UPS topology	Line-Interactive
Output power capacity	0.65 kVA
Output power	360 W
Waveform	Sine
Input operation voltage (min)	165 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Automatic Voltage Regulation (AVR)	Yes
Response time	4 ms
EMI/RFI noise filtering	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type E
AC outlets quantity	3 AC outlet(s)
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery recharge time	6 h
Design	
Form factor	Tower
Product colour	Black, Grey
Housing material	Plastic
Cable length	1.2 m
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%

Storage relative humidity (H-H)	0 - 90%
---------------------------------	---------

Operating altitude	0 - 3000 m
--------------------	------------

Non-operating altitude	0 - 3000 m
------------------------	------------

Certificates

Compliance certificates	RoHS
-------------------------	------

Certification	CE
---------------	----

Weight & dimensions

Width	84 mm
-------	-------

Depth	280 mm
-------	--------

Height	174 mm
--------	--------

Weight	3.8 kg
--------	--------

Matmenys ir svoris

Matmenys (I × P × A)	23,00cm × 31,00cm × 12,00cm
----------------------	-----------------------------

Svoris	4,00kg
--------	--------