

Ubiquiti Networks PBE-5AC-620 bridge/repeater 1000 Mbit/s

Gamintojas: **UBIQUITI** · Modelis: **PBE-5AC-620** · EAN: **810354022593** · Prekės kodas: **715305**

274,90 €

Kaina su PVM

Be PVM: **227,19 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

PBE-5AC-620 - Ubiquiti complete radio system

The Ubiquiti PBE-5AC-620 radio system is part of the AirMax NanoBeam M series. The device can work in Router or Bridge mode. It is characterised by 450 Mbps bandwidth.

The Ubiquiti PBE-5AC-620 device is protected from interference from other networks. This is why it can be placed in a location with more networks. The device works in the 5 GHz band.

Work

This product is equipped with a 720 MHz Atheros MIPS 74KC processor. The device uses 128 MB internal memory and 16 MB flash drive memory. The maximum data transfer speed of the device is 1000 Mbit/s. The device complies with the 802.11ac standard.

A range of capabilities

It is equipped with 1 Ethernet LAN (RJ-45) port. The maximum gain of the antenna is 29 dBi. The device supports PoE technology which is used to transfer power through Ethernet cables. The device is FCC, IC and CE certified.

Use

The PBE-5AC-620 can be used to create stable Point-to-Point links.

Installation

The installation of the Ubiquiti device is fast and efficient and does not require the use of specialised tools.

AirMax

The PowerBeam AC series products are based on AirMax technology which increases bandwidth and interference resistance as well as latency.

Key features

- works in the 5 GHz band
- 450+ Mbps bandwidth
- 30+ km range
- 29 dBi antenna gain
- durable construction
- AirMax technology
- InnerFeed technology
- Router or Bridge work mode

Construction

Durable construction combines with the use of the latest solutions resulting in a reliable and solid device. It can be used at temperatures ranging from -40 to 70 degrees Celsius.

Comparison

	PBE-5AC-300	PBE-5AC-400	PBE-5AC-500	PBE-5AC-620
FREQUENCY	5 GHz	5 GHz	5 GHz	5 GHz

THROUGHPUT	450+ Mbps	450+ Mbps	450+ Mbps	450+ Mbps
RANGE	20+ km	25+ km	25+ km	30+ km
GAIN	22 dBi	25 dBi	27 dBi	29 dBi
DISH REFLECTOR	300 mm	400 mm	500 mm	620 mmN
NETWORKING INTERFACE	(1) 10/100/1000 Ethernet Port	(1) 10/100/1000 Ethernet Port	(1) 10/100/1000 Ethernet Port	(1) 10/100/1000 Ethernet Port

Manufacturer's content

Read more in the manufacturer's documentation

Read the manual

Specifications

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][(-3085]
Matmenys ir svoris	
Matmenys (l × p × A)	71,00cm × 73,00cm × 22,00cm
Svoris	11,30kg