

APC SMT750RMI2UC nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 0,75 kVA 500 W 4 AC išvestis(ys / čių)

Gamintojas: **APC BY SCHNEIDER ELECTRIC** · Modelis: **SMT750RMI2UC** · EAN: **731304340324** · Prekės kodas: **715380**



775,90 €

Kaina su PVM

Be PVM: **641,24 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 0,75 kVA 500 W
- ✓ Signalų forma: Gryna sinusoidė
- ✓ 4 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Stelažas Juoda



SmartConnect Ethernet Port

For direct network-based power monitoring



Peace of mind at home or office with PowerChute™ Serial Shutdown Software



AVR : Automatic Voltage Regulation

Voltage fluctuations put your devices at risk. AVR instantly controls voltage to protect your equipment.



Aprašymas

Stay always online and prevent data loss

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software, you can even have critical IT hardware shut down automatically and in a controlled manner when the battery of the UPS is almost empty. This prevents data loss, downtime and physical damage to hardware.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. This makes it easy to see how long the UPS will supply emergency power at a certain load.

SmartConnect

Out-of-box remote UPS monitoring, free during a 6-month trial period. Using the SmartConnect Ethernet port, you can easily connect the Smart-UPS to your network and monitor it remotely via the secure APC SmartConnect cloud-based web portal*. In addition, the UPS can always be monitored via this port via EcoStruxure IT Expert (SFTWES1-DIGI).

* Extend access to SmartConnect via the following licenses:

1 year Standard Plan: ERWPMON1-1Y-DIGI

3 years Standard Plan: ERWPMON1-3Y-DIGI

1 year Advanced Plan: ERWPLUS1-1Y-DIGI

3 years Advanced Plan: ERWPLUS1-3Y-DIGI

PowerChute

By connecting the UPS to a maximum of one server via a USB cable, it can automatically provide it with a shutdown signal during a prolonged power failure and thus still prevent a hard shutdown. This exact moment can be set via the free APC PowerChute Serial Edition software.

Network Management Card

If you connect the UPS via the optional APC Network Management Card (AP9640/AP9641) directly to your network, it can be easily managed remotely via SNMP or our remote management software Ecostruxure IT Expert (SFTWES1-DIGI). You can also automatically send a shutdown signal via the network to multiple physical and/or virtual servers. By means of the APC PowerChute Network Shutdown Software belonging to the network card, it is even possible to differentiate the shutdown moment and the order in which this happens.

Ease of use

By means of physical buttons and an LCD screen, it is possible to set and read out the basic functionalities. Thanks to the supplied 4-post rail kit, you can easily mount the UPS in a rack.

Extend the lifespan

The internal battery cartridge (APCRBC123) can be replaced easily, safely and independently by the user. This without having to switch off the APC SMT750RMI2UC or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always stays online.

Warranty extension

The factory warranty of the SMT750RMI2UC is 3 years, with the exception of the battery cartridge, which has a factory warranty of 2 years. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-02).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If SmartConnect Advanced (ERWPLUS1-1Y-DIGI), a UPS with SmartConnect port + Ecostruxure IT Expert (SFTWES1-DIGI) or a network card (ap9640) in combination with Ecostruxure IT Expert (SFTWES1-DIGI) are used, this can even be done remotely.

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. The 750VA line interactive 2U rackmount UPS provides pure sine wave power to support critical electronics during power disruptions. It comes with IEC 320 C14 input, 4x IEC 320 C13 outlets, and 2x IEC jumper cables. It offers cloud-based remote power monitoring, UPS firmware upgrades, remote diagnostics and proactive email notifications with recommended actions. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. It provides surge protection against lightning strikes, power sags, brownouts and surges. The SMT UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. It is compatible with a dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications.

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	0,75 kVA
Išvesties galia	500 W
Signalų forma	Gryna sinusoidė
Išvesties eksploatacinė įtampa (min.)	151 V
Išvesties eksploatacinė įtampa (maks.)	302 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Automatinis įtampos reguliavimas (AVR)	Taip
Viršįtampio energijos įvertinimas	459 J
Išlaikymo trukmė (maks.)	2 ms
Efektyvumas	97,7%
Garso lygis	42 dB
Apsauga nuo viršįtampių	Taip

Garsiniai perspėjimo signalai	Taip
Automatinis paleidimas iš naujo	Taip
Ryšys	
AC išėjimo tipai	C13 šakotuvas
Maitinimo laido kištukas	C14 šakotuvas
Lizų kiekis	4 AC išvestis(ys / čių)
Išėjimo IEC jungčių skaičius	2
USB prievadas	Taip
Nuosekloji sąsaja	Taip
Nuosekliosios sąsajos tipas	RJ-45
„SmartSlot“	Taip
„SmartConnect“ prievadas	Taip
Baterija	
Baterijos technologija	Rūgštinis akumulatorius (VRLA)
Baterijos talpa	168 VAh
Tipiško laikino maitinimo trukmė pilna apkrova	5,5 min
Tipiško laikino maitinimo trukmė pusei apkrovimo	16 min
Baterijos veikimo trukmė (maks.)	5 metai
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip
Konstrukcija	
Forma	Stelažas
Produkto spalva	Juoda
Rėmo pajėgumas	2U
LED indikatoriai	Baterijos keitimas
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m

Sertifikatai

Atitikties sertifikatai	RoHS
Sertifikavimas	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, TUV, UL 1778, VDE, REACH, PEP, EOLi

Pakuotės turinys

Stovo montavimo rinkinys	Taip
Pridėti kabeliai	RS-232, USB laidas
Pridedama valdymo kortelė	Ne
Greito diegimo vadovas	Taip

Tvarumas

Tvarumo sertifikatai	Green Premium
----------------------	---------------

Svoris ir matmenys

Plotis	432 mm
Ilgis	406 mm
Aukštis	89 mm
Svoris	17,3 kg

Pakuotės duomenys

Programinės įrangos CD	Taip
Pakuotės plotis	546 mm
Pakuotės gylis	584 mm
Pakuotės aukštis	241 mm
Paketo svoris	21,2 kg

Logistikos duomenys

Gaminių skaičius ant padėklo	16 vnt
Darniosios sistemos (DS) kodas	85078000
Bendrasis anglies pėdsakas (kg of CO2e)	821,3

Matmenys ir svoris

Matmenys (I x P x A)	54,00cm x 57,00cm x 24,00cm
Svoris	22,00kg

Dokumentai ir vaizdo įrašai

[› Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 Reuil Malmaison, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt