

# TP-Link Omada Gigabit Single-Mode WDM Bi-Directional SFP Module

Gamintojas: **TP-LINK** · Modelis: **TL-SM321B-2** · EAN: **6935364072940** · Prekės kodas: **715569**



## 17,90 €

Kaina su PVM

Be PVM: **14,79 €**

**Sandėlyje**



**Prekė internetu**

Nuskuokite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ WDM Bi-Directional SFP Module
- ✓ Supports WDM Bi-Directional technology, using a single strand of fiber, cost saving
- ✓ Pairing with TL-SM321A or MC111CS
- ✓ Compatible with T3700 series, T2700 series, T2600 series, T2500 series, T1700 series, T1600 series, T1500 series, 2/3/5 series switches and MC220L



## Aprašymas

TP-LINK's TL-SM321B adopts the latest standard 1000Base-BX, transmission over a single strand of fiber, with one different wavelength going in each direction. You can extend the network distance up to 10Km(6.2 miles) with TP-LINK's Routers, Switches, Media Converters to provide high speed and stability.

## Techninė specifikacija

### Specifications

Sandėlio grupė

Networking [+782][-3085]

**Performance**

|                                                 |             |
|-------------------------------------------------|-------------|
| SFP transceiver type                            | Fiber optic |
| Maximum data transfer rate                      | 1250 Mbit/s |
| Interface type                                  | SFP         |
| Single-mode fiber (SMF) supported               | Yes         |
| Multi-mode fiber (MMF) supported                | No          |
| Fiber optic connector                           | LC          |
| Fiber cable diameters supported (core/cladding) | 9/125 µm    |
| SFP transceiver standard                        | BX          |
| Maximum transfer distance                       | 1000 m      |
| Tx wavelength (max)                             | 1310 nm     |
| Rx wavelength (max)                             | 1550 nm     |
| Networking standards                            | IEEE 802.3z |
| Wavelength-division multiplexing (WDM)          | Yes         |

**Features**

|                |          |
|----------------|----------|
| Product colour | Metallic |
|----------------|----------|

**Certificates**

|                         |         |
|-------------------------|---------|
| Compliance certificates | RoHS    |
| Certification           | FCC, CE |

**Operational conditions**

|                                   |             |
|-----------------------------------|-------------|
| Operating temperature (T-T)       | 0 - 70 °C   |
| Storage temperature (T-T)         | -40 - 80 °C |
| Operating relative humidity (H-H) | 10 - 90%    |
| Storage relative humidity (H-H)   | 5 - 90%     |

**Weight & dimensions**

|        |         |
|--------|---------|
| Width  | 55.4 mm |
| Depth  | 14.6 mm |
| Height | 12.9 mm |

**Packaging content**

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

**Packaging data**

|               |          |
|---------------|----------|
| User guide    | Yes      |
| Package width | 81.5 mm  |
| Package depth | 122.5 mm |

|                             |                           |
|-----------------------------|---------------------------|
| Package height              | 38.5 mm                   |
| Package weight              | 60 g                      |
| Logistics data              |                           |
| Harmonized System (HS) code | 85369010                  |
| Matmenys ir svoris          |                           |
| Matmenys (I × P × A)        | 8,00cm × 13,00cm × 4,00cm |
| Svoris                      | 0,10kg                    |