

# TP-Link 16-Port 10/100Mbps + 2-Port Gigabit Unmanaged PoE Switch

Gamintojas: **TP-LINK** · Modelis: **TL-SL1218MP** · EAN: **6935364099824** · Prekės kodas: **715823**



## 165,90 €

Kaina su PVM

Be PVM: **137,11 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 16 PoE+ 10/100Mbps RJ45 ports, 2 Gigabit RJ45 ports and 2 combo Gigabit SFP slots
- ✓ Up to 250m data and power transmission under extend mode specially designed for surveillance system
- ✓ Priority mode for port1-8 to guarantees the quality of sensitive applications like video monitor
- ✓ High PoE power budget with up to 30W for each PoE port and 194W for all PoE ports
- ✓ Easy to use, with no configuration and installation needed



## Aprašymas

### Easy to Use PoE Switch with Innovative Design

Up To 250m Data and Power Transmission for Surveillance

### High PoE Power Budget

TL-SL1218MP complies with the 802.3af/at PoE+ standard, supporting up to 30W power supply on each PoE port. The total high PoE power budget of up to 192W for the 16 PoE ports, making it ideal for small to medium business surveillance systems.

### Up to 250m Transmission for Surveillance

TL-SL1218MP is a special designed PoE switch for IP surveillance applications. PoE switch makes surveillance installation simpler, safer and less expensive. With the extend mode, the PoE transmission distance reaches up to 250m\* which makes it perfect for IP Camera deployment in large area coverage.

### Video Quality Guaranteed

Priority mode guarantees the important data, such as video surveillance, delivered with the best priority passing the data fabric even when the traffic load is heavy. Hardware switch for easy configuration with no login required.

## Techninė specifikacija

| Specifications                                |                                  |
|-----------------------------------------------|----------------------------------|
| Sandėlio grupė                                | Networking [+782][-3085]         |
| Management features                           |                                  |
| Switch type                                   | Unmanaged                        |
| Ports & interfaces                            |                                  |
| Basic switching RJ-45 Ethernet ports quantity | 16                               |
| Basic switching RJ-45 Ethernet ports type     | Fast Ethernet (10/100)           |
| Installed SFP+ modules quantity               | 0                                |
| Fast Ethernet (copper) ports quantity         | 16                               |
| Gigabit Ethernet (copper) ports quantity      | 2                                |
| Combo SFP ports quantity                      | 2                                |
| Network                                       |                                  |
| Networking standards                          | IEEE 802.3af, IEEE 802.3at       |
| 10G support                                   | No                               |
| Copper ethernet cabling technology            | 10BASE-T, 100BASE-TX, 1000BASE-T |
| Flow control support                          | Yes                              |
| Auto MDI/MDI-X                                | Yes                              |
| Data transmission                             |                                  |
| MAC address table                             | 8000 entries                     |
| Switching capacity                            | 7.2 Gbit/s                       |
| Store-and-forward                             | Yes                              |
| Jumbo frames support                          | Yes                              |
| Jumbo frames                                  | 10000                            |
| Packet buffer memory                          | 4.1 MB                           |
| Security                                      |                                  |
| MAC address filtering                         | Yes                              |
| Design                                        |                                  |

|                                                |                            |
|------------------------------------------------|----------------------------|
| Rack mounting                                  | Yes                        |
| Stackable                                      | No                         |
| Product colour                                 | Black                      |
| LED indicators                                 | LAN, PoE, Status           |
| Number of fans                                 | 2 fan(s)                   |
| <b>Power</b>                                   |                            |
| Power source                                   | AC                         |
| Power supply included                          | Yes                        |
| AC input voltage                               | 100 - 240 V                |
| AC input frequency                             | 50 - 60 Hz                 |
| Power consumption (typical)                    | 18.7 W                     |
| <b>Power over Ethernet (PoE)</b>               |                            |
| Power over Ethernet (PoE)                      | Yes                        |
| Power over Ethernet plus (PoE+) ports quantity | 16                         |
| Total Power over Ethernet (PoE) budget         | 192 W                      |
| <b>Operational conditions</b>                  |                            |
| Operating temperature (T-T)                    | 0 - 40 °C                  |
| Storage temperature (T-T)                      | -40 - 70 °C                |
| Operating relative humidity (H-H)              | 10 - 90%                   |
| Storage relative humidity (H-H)                | 5 - 90%                    |
| Heat dissipation                               | 741.15 BTU/h               |
| <b>Weight &amp; dimensions</b>                 |                            |
| Width                                          | 440 mm                     |
| Depth                                          | 180 mm                     |
| Height                                         | 44 mm                      |
| <b>Packaging content</b>                       |                            |
| Cables included                                | LAN (RJ-45)                |
| Quick start guide                              | Yes                        |
| User guide                                     | Yes                        |
| Manual                                         | Yes                        |
| <b>Logistics data</b>                          |                            |
| Harmonized System (HS) code                    | 85176990                   |
| <b>Matmenys ir svoris</b>                      |                            |
| Matmenys (I × P × A)                           | 54,00cm × 28,00cm × 8,00cm |

Svoris

3,30kg