

TP-Link JetStream 10-Port Gigabit Smart PoE Switch with 8-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **TL-SG2210MP** · EAN: **6935364030681** · Prekės kodas: **715824**



191,91 €

Kaina su PVM

Be PVM: **158,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 150 W PoE Budget: 8× 802.3at/af-compliant PoE+ ports with a total power supply of 150 W*
- ✓ Full Gigabit Ports: 8× gigabit PoE+ ports and 2× gigabit SFP Slots provide high-speed connections
- ✓ Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)**, Centralized Cloud Management, and Intelligent Monitoring
- ✓ Centralized Management: Cloud access and Omada app for ultra convenience and easy management
- ✓ Robust Security Strategies: IP-MAC-Port Binding, ACL, Port Security, DoS Defend, Storm Control, DHCP Snooping, 802.1X, Radius Authentication, and more
- ✓ Optimize Voice and Video Applications: L2/L3/L4 QoS and IGMP snooping



Aprašymas

Realize More Possibilities with Omada

JetStream 10-Port Gigabit Smart Switch with 8-Port PoE+

Software Defined Networking (SDN) with Cloud Access

Omada's Software Defined Networking (SDN) platform integrates network devices, including access points, switches and gateways, providing 100% centralized cloud management. Omada creates a highly scalable network—all controlled from a single interface. Seamless wireless and wired connections are provided, ideal for use in hospitality, education, retail, offices, and more.

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Management features	
Switch type	Managed
Switch layer	L2/L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
MIB support	RFC2925, RFC2618, RFC2620, RFC2021, RFC2819, RFC2674, RFC1213, RFC2233, RFC1643, RFC1493
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
SFP module slots quantity	2
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
VLAN support	Yes

Virtual LAN features	MAC address-based VLAN, Multicast VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN
Number of VLANs	4000
Optical fiber	
Fiber ethernet cabling technology	100BASE-FX, 1000BASE-X
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.9 Mpps
Number of queues	8
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	4.1 MB
Security	
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	EAP-LEAP, EAP-MD5, EAP-TLS, EAP-TTLS, HTTPS, SNMP, SNMPv2, SNMPv3, SSH, SSH-2, SSL/TLS
SSH/SSL support	Yes
BPDU filtering/protection	Yes
IP-MAC-Port binding	Yes
Queue scheduling algorithms	SP, Weighted Round Robin (WRR)
Multicast features	
Multicast support	Yes
Protocols	
Management protocols	SNMPv1/v2c/v3, SNMP
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Black
Number of fans	1 fan(s)
Power	
Power source	AC

Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	173.9 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	8
Total Power over Ethernet (PoE) budget	150 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	594.46 BTU/h
Weight & dimensions	
Width	294 mm
Depth	180 mm
Height	44 mm
Packaging data	
Package width	250 mm
Package depth	400 mm
Package height	80 mm
Package weight	2.12 kg
Certificates	
Certification	CE, FCC, RoHS
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	24,00cm × 40,00cm × 8,00cm
Svoris	2,50kg