APC UPS NTWK MGMT CARD POWERCHUTE

Gamintojas: **APC BY SCHNEIDER ELECTRIC** · Modelis: **AP9641** · EAN: **731304355540** · Prekės kodas: **715831**




422,90 €

Kaina su PVM

Be PVM: **349,50 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt












Aprašymas

Manage your Smart-UPS

With the ap9641 APC network card you connect an APC Smart-UPS (equipped with a SmartSlot) to the network. This way you can monitor and manage the UPS remotely (SNMP, EcoStruxure™ IT, web browser) and the UPS can send a shutdown signal to multiple physical and/or virtual servers using PowerChute Network Shutdown software.

Monitor the environment

The AP9641 includes one temperature sensor (AP9335T), allowing the ambient temperature of the UPS to be monitored remotely. An automatic temperature-initiated shutdown of the UPS is also possible.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Measure humidity

The AP9641 also offers space for a second sensor; if you choose the AP9335TH, you can monitor both the humidity and the temperature of the environment in which the UPS is located. This means that an automatic shutdown of UPS initiated by excessive humidity is also possible.

Wireless UPS monitoring via WiFi

By connecting the AP9834 APC USB Wi-Fi dongle to the network card, it can communicate wirelessly with your network.

Additional UPS monitoring via relay

Instead of a second sensor, you can also choose to combine the advantages of UPS monitoring via SNMP and potential-free / dry contacts. You do this by combining the ap9641 with the ap9810.

PowerChute Network Shutdown

PowerChute Network Shutdown is UPS management software that works with the UPS Network Management Card to protect Windows, Linux and Host ESXi, as well as hyperconverged and virtual infrastructure*. In the event of a power outage, PowerChute can properly shut down your virtual machines and the preconfigured boot sequence ensures they are turned back on.

*An additional license is required for HCI and virtual machine support:
1 year: SWPCNS1Y-DIGI
3 years: SWPCNS3Y-DIGI
5 years: SWPCNS5Y-DIGI

Remote management and monitoring of your network

The network card can be managed remotely via the easy-to-use web browser interface, remote management software EcoStruxure™ IT (SWITE1YR-DIGI) or other SNMP-compatible system. Tip EcoStruxure™ IT also includes the functionalities of the support contract below.

Support contract

The optional network card support contract license** ensures that you are always up to date and secure and includes additional benefits such as frequent updates with:
• New and improved features
• Security updates
• Advanced support

**The above license is included for the first year and available in the following variants:
1 year: SWNMC3SU-1Y-DIGI
3 years: SWNMC3SU-3Y-DIGI
5 years: SWNMC3SU-5Y-DIGI

Remote outlet switching

Stuck connected devices can be restarted remotely using controlled outlet groups already present on the UPS and in combination with a network card, so that functionality can be restored without the need to deploy personnel.

Remote monitoring service

The optional Schneider Electric EcoStruxure Asset Advisor service (WUPG1PEAA-UG-01) offers maximum protection and peace of mind by remotely monitoring critical equipment for you 24/7 in real time through SE's connected services hub. In the event of incidents, SE will contact you directly on your mobile phone via smart alarms and will also immediately provide problem solutions.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Asset Advisor is a cloud-based remote monitoring service that can monitor, troubleshoot and track site issues in a timely and efficient manner.

NMC specs

Processor: LCES (Low Cost Ethernet Solution)

Faster: Support up to 1Gbps

Storage: almost unlimited data & event logs

Ease of use: Pre-loaded language support & Micro USB based console

Techninė specifikacija

Savybės	
Gaminio tipas	Tinklo valdymo kortelė
Ryšys	
Priimančioji sąsaja	„SmartSlot“
Svoris ir matmenys	
Plotis	12,1 mm
Ilgis	11,4 mm
Aukštis	38 mm
Svoris	90 g
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85079080
Bendrasis anglies pėdsakas (kg of CO2e)	122,83
Matmenys ir svoris	
Matmenys (I × P × A)	17,00cm × 23,00cm × 5,00cm
Svoris	0,40kg

Dokumentai ir vaizdo įrašai

› Vaizdo įrašas objects.icecat.biz/objects/76756359_26784946.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 Rueil Malmaison, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt