

Samsung VM46B-U LCD Indoor

Gamintojas: **SAMSUNG** · Modelis: **LH46VMBUBGBXEN** · EAN: **8806094366082** · Prekės kodas: **715939**



1 325,91 €

Kaina su PVM

Be PVM: **1 095,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 116.8 cm (46") LCD
- ✓ 1920 x 1080 pixels Full HD
- ✓ 500 cd/m² 1200:1 0.53 x 0.53 mm
- ✓ Indoor Horizontal/Vertical Black
- ✓ VESA mounting 600 x 400 mm
- ✓ Ethernet LAN USB port
- ✓ 160 W



Aprašymas

Samsung VM46B-U. Display diagonal: 46", Display resolution: 1920 x 1080 pixels, Display technology: LCD, Display brightness: 500 cd/m², HD type: Full HD, Operating hours (hours/days): 24/7. Product color: Black

Techninė specifikacija

Specifications

Sandėlio grupė

Video Wall Displays [+1][-19]

Display

Display technology

LCD

Pixel pitch	0.53 x 0.53 mm
Display brightness	500 cd/m²
Display diagonal	116.8 cm (46")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Panel type	IPS
Aspect ratio	16:9
Pixel frequency	82 MHz
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	45000:1
Response time	0.008 s
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Horizontal scan range	62.7 - 72.3 kHz
Vertical scan range	57 - 63 Hz
Operating hours (hours/days)	24/7
Design	
Placement supported	Indoor
Orientation	Horizontal/Vertical
Bezel width (side)	1.25 mm
Bezel width (top)	2.25 mm
Bezel width (bottom)	2.25 mm
VESA mounting	Yes
Panel mounting interface	600 x 400 mm
Product colour	Black
Panel colour	Black
Ports & interfaces	
HDMI ports quantity	2
HDMI version	2
DVI port	Yes
DisplayPorts quantity	1
DisplayPort version	1.2
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
RS-232 input ports	1

RS-232 output ports	1
RS-232C	Yes
USB port	Yes
USB ports quantity	1
HDCP	Yes
HDCP version	2.2
IR input ports quantity	1
Audio input	Yes
Audio output	Yes

Power

Power consumption (typical)	160 W
Energy efficiency scale	A to G
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	128 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------

Sustainability

Certification	FCC (USA) Part 15, Subpart B Class ACE (Europe) : EN55032 : 2012 or 2015 EN55024:2010 or EN 55035:2017VCCI (Japan) : VCCI CISPR32:2016 Class BKCC/EK (Korea) : Tuner : KN13 / KN20Tunerless : KN22 / KN24BSMI (Taiwan) : CNS13438 (ITE EMI) Class A / CNS14336-1 (ITE Safety) / CNS15663 (RoHS)C-Tick (Australia) : AS/NZS CISPR32:2015CCC(China) :GB/T9254-2008, GB17625.1-2012GOST(Russia/CIS) : ROCT CISPR 24-2013/ROCT CISPR 22:2005
---------------	---

Weight & dimensions

Width	1022 mm
Depth	69.9 mm
Height	577 mm
Weight	15.7 kg

Packaging data

Package width	1193 mm
Package depth	257 mm

Package height	719 mm
----------------	--------

Package weight	22.2 kg
----------------	---------

Matmenys ir svoris

Matmenys (l × P × A)	71,00cm × 120,00cm × 26,00cm
----------------------	------------------------------

Svoris	22,20kg
--------	---------