

Dahua Technology PoE PFS3106-4ET-60-V2 network switch Unmanaged L2 Fast Ethernet (10/100) Black

Gamintojas: **DAHUA** · Modelis: **PFS3106-4ET-60-V2** · EAN: **6923172506603** · Prekės kodas: **715955**



93,90 €

Kaina su PVM

Be PVM: **77,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Eight-Pin assignment PoE power supply
- ✓ Intelligent PoE
- ✓ Hi-PoE 60W (Orange Port)
- ✓ PoE watchdog
- ✓ 250 m long distance PoE transmission
- ✓ Wide operating temperature: -30°C to +65°C (-22°F to +149°F)



Aprašymas

The **Dahua PFS3106-4ET-60-V2** is a state-of-the-art **4-Port PoE Switch** designed to meet the demands of modern networking environments. As an **Unmanaged Switch**, it offers plug-and-play functionality, making it ideal for users who require a hassle-free installation process. With its **Hi-PoE 60 W** capability on the orange port, this switch efficiently powers connected devices while ensuring reliable performance.

This model features **intelligent PoE** technology, which includes a **PoE watchdog** function that monitors the status of powered devices to ensure uninterrupted connectivity. Furthermore, it supports **250 m long distance PoE transmission**, enabling it to function effectively even in large installations. The device operates within a wide temperature range of **-30 °C to +65 °C**, making it suitable for various environmental conditions.

Manufactured by the reputable company **Dahua**, the PFS3106-4ET-60-V2 switch stands out with its advanced features and reliability. It is an essential component for users seeking to enhance their network infrastructure while ensuring robust power delivery and communication capabilities.

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Management features	
Switch type	Unmanaged
Switch layer	L2
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	4
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	1
Installed SFP+ modules quantity	0
Fiber ports quantity	1
Fiber optic connector	SFP
Network	
Ethernet LAN data rates	10,100,1000 Mbit/s
Optical fiber	
Fiber ethernet cabling technology	100BASE-X, 1000Base-X
Data transmission	
MAC address table	8000 entries
Switching capacity	6.8 Gbit/s
Forwarding rate	3.57 Mpps
Store-and-forward	Yes
Packet buffer memory	1 MB
Design	
Product colour	Black

Housing material	Metal
LED indicators	Power, Status
DIN rail mounting	Yes
Power	
Power source	DC
Power consumption (typical)	3 W
Operational conditions	
Operating temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	150 mm
Depth	100 mm
Height	30 mm
Weight	450 g
Packaging content	
Manual	Yes
Packaging data	
Package width	270 mm
Package depth	240 mm
Package height	75 mm
Package weight	1.1 kg
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 15,00cm × 3,00cm
Svoris	0,45kg