

TP-Link TL-SG1210MP network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **TP-LINK** · Modelis: **TL-SG1210MP** · EAN: **6935364052683** · Prekės kodas: **715974**



110,90 €

Kaina su PVM

Be PVM: **91,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 9
- ✓ Cat3, Cat4, Cat5, Cat5e 10BASE-T, 100BASE-TX
- ✓ MAC address table: 4000 entries
- ✓ Switching capacity: 20 Gbit/s
- ✓ DC Power over Ethernet (PoE)



Aprašymas

The **TP-Link TL-SG1210MP** is an advanced **unmanaged switch** designed to enhance network connectivity with its **10 Gigabit Ethernet ports**. Among these, **8 ports** support **Power over Ethernet (PoE+)**, allowing for the simultaneous delivery of power and data through a single cable. This capability makes the TL-SG1210MP an ideal choice for powering **PoE-enabled devices** such as **IP cameras**, **VoIP phones**, and **wireless access points**, eliminating the need for additional power supplies and simplifying installation.

Equipped with a total of **9 RJ-45 Ethernet ports** that support **gigabit speeds** (10/100/1000 Mbps), the TL-SG1210MP significantly enhances network capacity and data transfer rates. With a **switching capacity of 20 Gbit/s** and a **MAC address table** that can store up to **4000 entries**, this switch ensures smooth and efficient data transmission, even in high-traffic environments. The device adheres to multiple networking standards, including **IEEE 802.3af**, **IEEE 802.3at**, **IEEE 802.3i**, **IEEE 802.3u**, **IEEE 802.3x**, and **IEEE 802.3z**, ensuring broad compatibility with various network protocols and devices.

The **TP-Link TL-SG1210MP** is an effective solution for expanding network connections in **homes, small offices, or enterprise environments**. Its robust design and advanced features make it a reliable choice for users seeking to optimize their network infrastructure. With its ability to power devices directly through the network cable, the TL-SG1210MP stands out as a superior option compared to traditional switches, providing both efficiency and convenience in one compact unit.

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][−3085]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	9
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Combo SFP ports quantity	1
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	20 Gbit/s
Store-and-forward	Yes
Packet buffer memory	14.88 MB
Design	
Rack mounting	No
Product colour	Black

LED indicators	Yes
Performance	
Fanless	Yes
Power	
Power source	DC
Input current	2.43 A
Input voltage	53.5 V
Power consumption (max)	141.4 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	123 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	482.17 BTU/h
Weight & dimensions	
Width	209 mm
Depth	126 mm
Height	26 mm
Packaging content	
Quick start guide	Yes
Packaging data	
Package width	240 mm
Package depth	315 mm
Package height	70 mm
Package weight	1.41 kg
Certificates	
Certification	CE, FCC
Logistics data	
Harmonized System (HS) code	85176990

Matmenys ir svoris

Matmenys (l × p × A)15,00cm × 32,00cm × 8,00cm

Svoris1,60kg