

CyberPower PDU44005 power distribution unit (PDU) 10 AC outlet(s) 1U Black

Gamintojas: **CYBERPOWER** · Modelis: **PDU44005** · EAN: **4711027799780** · Prekės kodas: **716308**



544,90 €

Kaina su PVM

Be PVM: **450,33 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Real-time Local/Remote Monitoring and Switching
- ✓ Dual Inputs
- ✓ Industrial-grade Metal Housing
- ✓ User Configurable Color LCD
- ✓ LED Status Indicator
- ✓ Support Environmental Sensor
- ✓ PowerPanel Management Software
- ✓ Cord Retention Tray
- ✓ Controllable Receptacles with Power Sequencing
- ✓ Quick Transfer Time (Total $\leq$ 10 ms)



Aprašymas

CyberPower PDU44005 provides output from a UPS unit, generator, or utility power to multiple connected devices in IT environments. Dual power cords can be plugged into separate power sources to provide redundancy to single-corded connected equipment. If the selected power source exceeds the desired thresholds or fails, the ATS PDU will automatically switch to the other power source to ensure continuous operation. The unit supports remote individual outlet control over the network, allowing administrators to turn on/off connected devices from any location.

The product is built-in with hot-swappable Ethernet module, which can work with PowerPanel® Power Management Software and power management web interface for real-time remote monitoring and configuration. The digital LCD display is also color configurable, allowing users to easily maintain and monitor the ATS PDU. Users can change LCD's colors to easily categorize devices between multiple machines in server room and

IT environments. Event logging via a web browser or network connection allows users to review the history of power conditions. When specified power events occur, automatic event notifications will be sent via email, SMS text, or SNMP trap to designated users so that they can take immediate actions. The USB port also supports easy firmware upgrade. Moreover, the featured RJ45 port enables the connection of the optional environmental sensor (ENVIROSENSOR), which can provide real-time temperature and humidity monitoring in an IT center.

Techninė specifikacija

Specifications	
Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
Design	
PDU types	Managed, Monitored, Switched
Rack capacity	1U
Type	Single-phase
Mounting	Horizontal
Housing material	Steel
Product colour	Black
Display	LCD
Ports & interfaces	
AC outlets quantity	10 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 60320
Ethernet LAN (RJ-45) ports	4
USB ports quantity	1
Features	
Daisy chain	Yes
LED indicators	Yes
Cable length	3.05 m
Management features	
Monitoring	Current, Power, Voltage
Supported network protocols	IPv4/v6, SNMPv1/v3, HTTP/HTTPS, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and Syslog
Firmware upgradeable	Yes
Power	
Nominal input voltage	200 - 240 V
Maximum current	16 A
AC input frequency	50 - 60 Hz

Certificates

Compliance certificates	CE, RoHS
Certification	CE, FCC Class A, UL62368, EN 55032 Class A, IEC 62368

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-15 - 55 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 4000 m
Non-operating altitude	0 - 15000 m

Weight & dimensions

Width	433 mm
Depth	215 mm
Height	44 mm
Weight	3.4 kg

Packaging content

Cables included	Serial
Manual	Yes
Rack mount kit	Yes

Packaging data

Package weight	6 kg
Package width	500 mm
Package depth	398 mm
Package height	125 mm

Logistics data

Country of origin	China
-------------------	-------

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	40,00cm × 13,00cm × 55,00cm
Svoris	6,00kg