

CyberPower OLS2000ERT2UA uninterruptible power supply (UPS) Double-conversion (Online) 2 kVA 1800 W 8 AC outlet(s)

 Gamintojas: **CYBERPOWER** · Modelis: **OLS2000ERT2UA** · EAN: **4712856273816** · Prekės kodas: **716309**


544,90 €

Kaina su PVM

 Be PVM: **450,33 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Extended Battery Module Auto-detection
- ✓ Critical/Non-critical Load Outlets
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ Variable Speed Fans
- ✓ PowerPanel® Management Software
- ✓ Rack/Tower Convertible Configurations



Aprašymas

CyberPower OLS2000ERT2UA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS features color LCD panel for users to monitor power system and configure settings easily, and relay-type dry contact to perform local management. This model is designed with extended battery module auto-detection, which can automatically detect the quantity of connected Extended Battery Modules (EBM) to estimate UPS's runtime. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	2 kVA
Output power	1800 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Maximum current	9 A
Surge energy rating	363 J
Response time	0 ms
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.99
Crest factor	3:1
ECO mode	Yes
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Noise level	45 dB
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
Modem (RJ-11) ports	1
Ethernet LAN (RJ-45) ports	1

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	4
Typical backup time at full load	3.8 min
Typical backup time at half load	13.1 min
Charging current	1.5 A
Hot-swap battery	Yes

Design

Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Cable length	1.5 m
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m

Certificates

Certification	CE, EAC, RoHS
---------------	---------------

Packaging content

Cables included	USB cable
-----------------	-----------

Weight & dimensions

Width	438 mm
Depth	430 mm
Height	88 mm
Weight	17.1 kg

Packaging data

Package width	540 mm
---------------	--------

Package depth	550 mm
Package height	230 mm
Package weight	21.9 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Matmenys (I × P × A)	55,00cm × 56,00cm × 23,00cm
Svoris	23,30kg