

TP-Link Omada AX1800 Indoor/Outdoor Wi-Fi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP623-Outdoor HD** · EAN: **4895252506303** · Prekės kodas: **716573**



222,89 €

Kaina su PVM

Be PVM: **184,21 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Up to 1.8 Gbps WiFi 6 Speeds: 574 Mbps on 2.4 GHz + 1201 Mbps on 5 GHz
- ✓ Supports WiFi 6 technologies, such as HE160, 1024-QAM, etc
- ✓ High-density connectivity up to 1,000+ clients
- ✓ Long-range coverage with the high-power amplifier and smart antennas
- ✓ Advanced Functions: Centralized management, Omada mesh, and seamless roaming
- ✓ PoE+ Powered: Supports both 802.3at PoE (adapter not included)



Aprašymas

Long-Range, High-Speed WiFi 6

Professional antennas with high-power amplifiers utilize WiFi 6 technology to deliver robust and extensive wireless coverage.

Powered by the latest WiFi 6 technology, the AP delivers speeds of up to 1.8 Gbps.

Explore More with Smart Antennas

Equipped with horizontally polarized and vertically polarized antennas, EAP623-Outdoor HD's intelligent algorithms automatically select the optimal antennas, bringing lower interference, longer coverage, and higher performance.

Ideal for High-Density Outdoor Scenes

OFDMA and MU-MIMO provide simultaneous connections for dozens of clients in large open areas.

Equipped with an IP67 weatherproof enclosure, our EAP623-Outdoor HD withstands the most extreme environments.

Flexible Deployment with Omada Mesh and PoE Support

Seamless Integration into Omada SDN

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1800 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	1201 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
Number of users	1020 user(s)
Automatic channel selection	Yes
Automatic channel scanning	Yes
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Rate limiting	Yes
Band steering	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	< 20 dBm (2.4 GHz, EIRP), < 30 dBm (5 GHz, EIRP);
Transmitting power (FCC)	< 25 dBm (2.4 GHz), < 25 dBm (5 GHz)
Security	
Security algorithms	SNMP, SNMPv2, SNMPv3, SSH
MAC address filtering	Yes

Remote Authentication Dial-In User Service (RADIUS)	Yes
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Design	
Placement	Pole
Product colour	White
Reset button	Yes
LED indicators	Yes
Antenna	
Antenna type	Internal
Antenna direction type	Omni-directional
Antenna features	Integrated antenna
Antennas quantity	2
Certificates	
Certification	CE, FCC, RoHS
Weight & dimensions	
Width	280.4 mm
Depth	106.5 mm
Height	56.8 mm
Packaging content	
Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	-30 - 70 °C

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Matmenys ir svoris

Matmenys (l × P × A)	24,00cm × 33,00cm × 7,00cm
----------------------	----------------------------

Svoris	1,30kg
--------	--------