

Dahua Technology WizSense IPC-HDBW2441R-ZAS-27135 Dome IP security camera Outdoor 2688 x 1520 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **IPC-HDBW2441R-ZAS-27135** · EAN: **6923172545671** · Prekės kodas: **716724**



185,90 €

Kaina su PVM

Be PVM: **153,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 (2560 × 1440)@25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED, and the max. illumination distance is 40 m
- ✓ ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC
- ✓ 12 VDC/PoE power supply, easy for installation



Aprašymas

Equipped with advanced Dahua technology, the WizSense IPC-HDBW2441R-ZAS-27135 is a high-definition IP security camera designed for outdoor use. This wired camera features a 4MP sensor that delivers clear and detailed images, ensuring comprehensive surveillance coverage. The device supports a vari-focal lens, allowing for adjustable field of view to suit different monitoring needs.

The camera is housed in a durable, white dome casing that offers protection against environmental elements, making it suitable for ceiling installation. It incorporates IR capabilities with a range that ensures visibility in low-light conditions up to distances typical of outdoor environments. Additionally, the camera is equipped with a 120 dB wide dynamic range that enhances image quality under varied lighting conditions.

This model is part of the WizSense series, which is designed to provide intelligent sensing in security applications, distinguishing between human and vehicular figures to reduce false alarms and enhance perimeter protection. The integration capabilities and robust construction make it a dependable choice for enhancing security in diverse settings.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Dynamic range	120 dB
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Camera	
Minimum illumination	0 lx
Angle of rotation	355°
Lens viewing angle, horizontal	104 - 29°
Lens viewing angle, vertical	54 - 16°
Lens viewing angle, diagonal	125 - 34°
Tilt angle range	0 - 75°
Pan range	0 - 355°
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s

Adjustment shutter speed	Auto/Manual
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Progressive scan	Yes
Lens system	
Focal length range	2.7 - 13.5 mm
Minimum aperture number	1.5
Detect distance (wide)	64 m
Detect distance (tele)	210 m
Observe distance (wide)	25.6 m
Observe distance (tele)	84 m
Recognize distance (wide)	12.8 m
Recognize distance (tele)	42 m
Identify distance (wide)	6.4 m
Identify distance (tele)	21 m
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	40 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	2688 x 1520 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	12 kbps–6144 kbps
Back Light Compensation (BLC)	Yes

Highlight Compensation (HLC)	Yes
Audio	
Built-in speaker(s)	Yes
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711 A-law, G.711 μ -law, G.726, PCM
Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Number of users	6 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Flash memory	128 MB
Internal memory	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Alarm input channels	1
Alarm output channels	1
Video motion detection	Yes
Mirror	Yes
Management features	
Web browser	No
Management software	Smart PSS; DSS; DMSS
Power	
Power source type	DC, PoE

Power consumption (typical)	2.3 W
Power consumption (max)	6.5 W
Power consumption (Power over Ethernet (PoE))	3.2 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Height	93.4 mm
Diameter	12.2 cm
Weight	520 g
Packaging data	
Package weight	680 g
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 16,00cm × 13,00cm
Svoris	0,70kg