

Dahua Technology WizSense IPC-HDBW2541R-ZAS Dome IP security camera Indoor & outdoor 2592 x 1944 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **IPC-HDBW2541R-ZAS-27135-S2** · EAN: **6923172581761** · Prekės kodas: **716728**



181,90 €

Kaina su PVM

Be PVM: **150,33 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 5 MP (2592 × 1944) @20 fps, and supports 4 MP (2688×1520) @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED, and the max. illumination distance is 40 m
- ✓ ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, video tampering, scene changing, audio detection (Only - ZAS supports) , no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports)
- ✓ Supports max. 256 G Micro SD card



Aprašymas

5MP IR Vari-focal Dome WizSense Network Camera

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes
Dynamic range	120 dB
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Camera	
Minimum illumination	0 lx
Angle of rotation	360°
Lens viewing angle, horizontal	100 - 30°
Lens viewing angle, vertical	72 - 23°
Lens viewing angle, diagonal	134 - 38°
Tilt angle range	0 - 75°
Pan range	0 - 355°
White balance	Auto, Natural, Outdoor, Regional custom, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1/3 -1/100000 s
Adjustment shutter speed	Auto/Manual
Number of Privacy masking areas	4
Image sensor	

Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Number of effective pixels (H x V)	2592 x 1944 pixels
Panoramic camera	
Signal-to-Noise Ratio (SNR) (panoramic camera)	56 dB
Bit rate control (panoramic camera)	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Lens system	
Focal length range	2.7 - 13.5 mm
Detect distance (wide)	64.4 m
Detect distance (tele)	221.4 m
Observe distance (wide)	25.8 m
Observe distance (tele)	88.6 m
Recognize distance (wide)	12.9 m
Recognize distance (tele)	44.3 m
Identify distance (wide)	6.4 m
Identify distance (tele)	22.1 m
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	40 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	2592 x 1944 pixels
Total megapixels	5 MP
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+, M-JPEG
Supported graphics resolutions	704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2592 x 1944, 2688 x 1520
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual

Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	H.264: 3 kbps–8192 kbps H.265: 3 kbps–8192 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Audio input channels	2.0 channels
Audio output channels	2.0 channels
Audio formats supported	G.711 A-law, G.726, PCM
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Number of users	20 user(s)
Storage	
Built-in HDD	No
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	512 MB
ROM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Video motion detection	Yes
Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Mirror	Yes
Management features	
Web browser	Yes
Management software	Smart PSS; DSS; DMSS
Power	

Power source type	DC, PoE
Power consumption (typical)	3.1 W
Power consumption (Power over Ethernet (PoE))	4 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Height	88.9 mm
Diameter	12.2 cm
Weight	492 g
Packaging data	
Package weight	663 g
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 16,00cm × 14,00cm
Svoris	0,70kg