

Dahua Technology IPC-HFW2849T-AS-IL-0360B security camera

Bullet IP security camera Indoor & outdoor 3840 x 2160 pixels

Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **IPC-HFW2849T-AS-IL-0360B** · EAN: **6923172590084** · Prekės kodas: **716734**



194,89 €

Kaina su PVM

Be PVM: **161,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m
- ✓ ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in MIC
- ✓ 12 VDC/PoE power supply, easy for installation



Aprašymas

Launched by Dahua Technology, WizSense is a series of wide range AI products and solutions that adopt independent AI chip and deep learning algorithm. It can recognize human and vehicle in an image with high accuracy, enabling users to focus on real targets. WizSense focuses on human and vehicle, benefiting everyone with intelligent functions, simple configuration and inclusive products.

Intelligent: Powered by AI chip and deep learning algorithm, WizSense provides various features that realizes accurate alarms for human and vehicle, and quick target search, maximizing resources to increase overall efficiency.

Simple: WizSense offers simple configuration, especially for SMD and AI Coding enabled by default. It eases your customer's daily job and also empowers them to make better business decisions.

Inclusive: Inclusivity of WizSense is the idea that everyone gets the opportunities and benefits from AI. With affordable prices and easy configuration of Dahua WizSense, AI is no longer confined to an ivory tower, but applied to real scenarios instead.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes
Built-in light	Yes
Dynamic range	120 dB
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B; UL/CUL: UL62368-1 & CAN/CSA C22.2 No. 62368-1-14
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Form factor	Bullet
Housing material	Metal
Protection features	Corrosion resistant, Waterproof
International Protection (IP) code	IP67
IK code	IK10
Camera	
Minimum illumination	0 lx
Angle of rotation	360°

Lens viewing angle, horizontal	55°
Lens viewing angle, vertical	31°
Lens viewing angle, diagonal	62°
Tilt angle range	0 - 90°
Pan range	0 - 360°
White balance	Auto, Manual, Natural, Outdoor, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Detect distance	154.7 m
Observe distance	61.9 m
Recognize distance	30.9 m
Maximum aperture number	1.6
Identify distance	15.5 m
Fixed focal length	3.6 mm
Closest focusing distance	3.5 m
Night vision	
Night vision	Yes
Night vision distance	50 m
B/W night vision distance	60 m
LED type	IR/White
Number of illumination LEDs	4
Video	
Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.264+, H.264B, H.265, H.265+

Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2688 x 1512, 2880 x 1620, 3072 x 1728, 3072 x 2048, 3840 x 2160
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	12 Kbps - 8192 Kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes

Audio

Audio input channels	1.0 channels
Audio output channels	1.0 channels
Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Voice codecs	G.711Mu, G.711a, G.726, PCM

Network

Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour; P2P
Number of users	20 user(s)
Client interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone

Storage

Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB

ROM capacity	128 MB
RAM capacity	256 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Alarm input channels	1
Alarm output channels	1
Video motion detection	Yes
Privacy protection	Yes
Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Mirror	Yes
Network access storage (NAS)	Yes
Management features	
Web browser	Yes
Management software	Smart PSS, DSS, DMSS
Power	
Power source type	DC, PoE
Power consumption (typical)	2.6 W
Power consumption (max)	7 W
Power consumption (Power over Ethernet (PoE))	8.3 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Width	90.7 mm
Height	90.7 mm
Length	238.5 mm
Weight	720 g
Packaging data	

Package weight	970 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---

Other features

Browser supported	IE: IE8, IE9, IE11 Chrome Firefox, Safari
-------------------	---

Technical details

Lens mount interface	M12
----------------------	-----

Number of video streams	2
-------------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	16,00cm × 31,00cm × 15,00cm
----------------------	-----------------------------

Svoris	1,00kg
--------	--------