

Dahua Technology WizSense SD3E405DB-GNY-A-PV1 Turret IP security camera Indoor & outdoor 2560 x 1440 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **SD3E405DB-GNY-A-PV1** · EAN: **6923172548184** · Prekės kodas: **716735**



301,90 €

Kaina su PVM

Be PVM: **249,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/2.8" 4Megapixel CMOS
- ✓ 5x optical zoom
- ✓ Max. 25/30fps@4M
- ✓ IR distance up to 50 m
- ✓ Warm light illumination distance up to 30 m
- ✓ SMD 3.0
- ✓ Perimeter protection
- ✓ Face detection
- ✓ Alarm: 1 in, 1 out; audio: 1 in, 1 out
- ✓ Built-in Mic and Speaker for Two-way Talk



Aprašymas

Equipped with a 4-megapixel sensor, this network PTZ camera delivers high-resolution video footage, ensuring detailed image quality for security monitoring. The camera features a 5x optical zoom capability, allowing for closer views and more precise details of distant objects without compromising image clarity. It incorporates WizSense technology, which enhances its intelligence and efficiency, particularly in recognizing human and vehicular targets.

This model is designed with TiOC (Three-in-One Camera) functionality that integrates full-color monitoring, active deterrence, and AI-powered features to streamline incident response and reduce false alarms. The active deterrence system includes both audio and visual alarms to discourage unauthorized activities as soon as they are detected.

The camera supports various video compression standards including H.265, H.264, and MJPEG, optimizing storage and bandwidth use while maintaining high-quality video output. It is built to withstand outdoor environments with a robust construction that is both water and dust resistant, adhering to IP66 standards. The device also offers flexible connectivity options, ensuring compatibility with a variety of networks and setups.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
PTZ control	Yes
Auto-tracking	Yes
Preset points	Yes
Wide Dynamic Range (WDR)	Yes
Certification	CE: EN55032/EN55024/EN50130-4 FCC: Part15 B, ANSI C63.4-2014
Design	
Mounting type	Ceiling/wall
Product colour	White
Form factor	Turret
International Protection (IP) code	IP66
Camera	
Minimum illumination	0.0005 lx
Tilt angle range	-15 - 90°
Tilt speed	25.8 °/sec
Tilt preset speed	27.1 °/sec
Pan range	0 - 355°

Pan speed	36 °/sec
Pan preset speed	35.7 °/sec
White balance	Indoor, Manual, Natural, Outdoor, Sodium lamp, Street lamp
Camera shutter speed	1/1 - 1/30000 s

Image sensor

Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes

Lens system

Number of lenses	1
Zoom capability	Yes
Optical zoom	5x
Digital zoom	16x
Detect distance	270 m
Observe distance	106.6 m
Recognize distance	54 m
Focal length range	2.7 - 13.5 mm
Auto focus	Yes
Focus	Motorized/Manual
Maximum aperture number	3
Identify distance	27 m
Minimum aperture number	1.6
Closest focusing distance	1.5 m

Night vision

Night vision	Yes
Night vision distance	50 m
Number of illumination LEDs	6
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264+, H.264B, H.265, H.265+, M-JPEG
Supported graphics resolutions	352 x 288, 640 x 480 (VGA), 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	2D noise reduction, 3D noise reduction
Image stabilizer	Yes
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Audio input channels	1.0 channels

Audio output channels	1.0 channels
Signal-to-Noise Ratio (SNR)	55 dB
Voice codecs	G.711Mu, G.711a, G.722.1, G.726, MP2L2, PCM
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Supported network protocols	FTP;RTMP;IPv6;Bonjour;IPv4;DNS;RTCP;PPPoE;NTP;RTP;802.1x;HTTPS;SNMP;TCP/IP;DDNS;UPnP;NFS;ICMP;UDP;IGMP;SMB;HTTP;SSL;DHCP;SMTP;QoS
Number of users	20 user(s)
Streaming method	Multicast, Unicast
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
ROM capacity	128 MB
RAM capacity	512 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Alarm input channels	1
Alarm output channels	1
Video motion detection	Yes

Active
tampering
alarm

Yes

Intelligent
Video
Surveillance
(IVS) system
features

Abandoned object, Face detection, Human detection, Intrusion, Missing object, Tripwire, Vehicle detection

Management features

Management
software

DMSS;DSS Pro

Power

Power source
type

DC, PoE

Power
consumption
(typical)

4.5 W

Power
consumption
(max)

15 W

DC output
voltage

12

Operational conditions

Operating
temperature
(T-T)

-30 - 60 °C

Operating
relative
humidity (H-
H)

0 - 95%

System requirements

Mobile
operating
systems
supported

Android, iOS

Weight & dimensions

Width

140 mm

Depth

142.6 mm

Height

236.1 mm

Weight

1.5 kg

Packaging data

Package weight 2.1 kg

Packaging content

Number of cameras 1

Matmenys ir svoris

Matmenys (l x P x A) 25,00cm x 29,00cm x 19,00cm

Svoris 2,10kg