

Dahua Technology Mobile Camera DH-IPC-HDBW1430DE-SW security camera Dome IP security camera Indoor & outdoor 2560 x 1440 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **IPC-HDBW1430DE-SW-0280B** · EAN: **6923172539984** · Prekės kodas: **716736**



105,90 €

Kaina su PVM

Be PVM: **87,52 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-MP 1/3" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 4 MP (2560 × 1440)@20 fps, and max. supports 3 MP (2304 × 1296)@25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED
- ✓ SMART H.264 +/H.265+, flexible coding, applicable to various band width and storage environments
- ✓ DWDR, 3D NR, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, SMD (human)
- ✓ Supports single antenna 2.4G Wi-Fi that covers a range of up to 80 m in an open area
- ✓ Supports max. 256 G Micro SD card
- ✓ 12 VDC power supply



Aprašymas

This dome network camera features a 4-megapixel resolution, delivering high-quality, clear images for security monitoring. It is equipped with infrared capabilities, ensuring effective surveillance even in low-light conditions up to a distance of 30 meters. The camera's fixed-focal lens has a

2.8mm focal length, providing a wide-angle view that is suitable for monitoring large areas.

Designed for both indoor and outdoor use, the camera boasts an IP67 rating, making it resistant to dust and water, which ensures continued operation in adverse weather conditions. The Wi-Fi connectivity allows for wireless installation, reducing the need for extensive wiring and enabling flexible placement options.

The device supports H.265 compression technology, which helps in reducing bandwidth and storage requirements while maintaining high-quality video output. It also features motion detection technology, which triggers recording and alerts when movement is detected, enhancing the security measures of the monitored area.

This camera is compatible with iOS and Android devices through a dedicated app, facilitating remote viewing and management of video feeds from smartphones and tablets.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired & Wireless
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Remote viewing	Yes
Antenna type	External
Antennas quantity	1
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU; FCC: 47 CFR FCC Part 15, Subpart B; FCC ID: FCC PART 15C
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Camera	
Angle of rotation	355°
Lens viewing angle, horizontal	90°
Tilt angle range	0 - 75°

Pan range	0 - 355°
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	Yes
Panoramic camera	
Digital Wide Dynamic Range (DWDR) (panoramic camera)	Yes
Lens system	
Number of lenses	1
Detect distance	68 m
Observe distance	27.2 m
Recognize distance	13.6 m
Auto focus	Yes
Maximum aperture number	2
Identify distance	6.8 m
Fixed focal length (thermal module)	2.8 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Number of illumination LEDs	3
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video formats supported	H.264, H.264B, H.265
Video compression formats	H.264+, H.264H, H.265+
Supported graphics resolutions	1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440
Supported video modes	720p, 1080p
Video recording	Yes
Frame rate	30 fps

Video intelligence analytic	Yes
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	3 Kbps - 20480 Kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Smart IR	Yes
Audio	
Audio system	1-way
Audio system full duplex	Yes
Audio codecs	G.711a; G.711Mu; PCM; G.726; G.723
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Bluetooth	No
Ethernet interface type	Fast Ethernet
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Number of users	6 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	64 MB
ROM capacity	16 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Detection distance	80 m
Intelligent Video Surveillance (IVS) system features	Intrusion
Mirror	Yes

Management features

Web browser	Yes
-------------	-----

Power

Power source type	DC, PoE
-------------------	---------

DC output voltage	12
-------------------	----

Operational conditions

Operating temperature (T-T)	-40 - 60 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Operating relative humidity (H-H)	0 - 95%
-----------------------------------	---------

System requirements

Mobile operating systems supported	Android, iOS
------------------------------------	--------------

Weight & dimensions

Height	88.7 mm
--------	---------

Diameter	11.1 cm
----------	---------

Weight	414 g
--------	-------

Packaging data

Package weight	592 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	14,00cm × 14,00cm × 12,00cm
----------------------	-----------------------------

Svoris	0,60kg
--------	--------