

Dahua Technology Lite NVR2108-4KS3 network video recorder 1U Black

Gamintojas: **DAHUA** · Modelis: **NVR2108-4KS3** · EAN: **6923172507846** · Prekės kodas: **716741**



85,90 €

Kaina su PVM

Be PVM: **70,99 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats
- ✓ Max. decoding capability: 6 × 1080p@30 fps
- ✓ Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth
- ✓ Supports IP cameras with a resolution up to 12 MP
- ✓ AI by Recorder supports 4-channel SMD
- ✓ AI by Camera supports perimeter protection and SMD
- ✓ Supports one-click arming and disarming



Aprašymas

The NVR2000-4KS3 model of the Lite Series NVR is favored for its outstanding performance. It supports 4K resolution for scenes that require highly detailed images, and can serve as the edge, central, or backup storage with an intuitive shortcut menu for remote management and control. This NVR also features Smart Motion Detection (SMD) by recorder, which can distinguish target vehicles and humans from ordinary ones in real-time. This NVR is both cost-effective and easy-to-install, making it ideal for a wide range of applications such as villas, shops and other small and medium-sized scenes.

SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion

detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

Perimeter Protection by Camera

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Video input channels	4 channels
Maximum resolution	3840 x 2160 pixels
Video recording modes	720p, 960p, 1080p
Supported resolutions	HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Video motion detection	Yes
Audio formats supported	G.711 A-law, G.711 μ-law, G.726, PCM
Video formats supported	H.264, H.264+, H.265, H.265+
Image formats supported	MJPEG
Operating system installed	Embedded LINUX
Input bandwidth	80 Mbit/s
Output bandwidth	60 Mbit/s
Wireless LAN features	
Wi-Fi	No
Hard drive	
Maximum storage capacity	20 TB
HDD interface	SATA
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Yes
Ethernet LAN data rates	10,100 Mbit/s
Power over Ethernet (PoE) ports quantity	8
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	2
Audio RCA inputs	1

Audio RCA outputs	1
eSATA ports quantity	1
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	HTTP; HTTPS; TCP/IP; IPv4; IPv6; UDP; NTP; DHCP; DNS; SMTP; IP Filter; DDNS; IP Search (Supports IP camera, DVR, NVS, etc.); P2P; Auto Registration
Features	
Rack mounting	Yes
Rack capacity	1U
Product colour	Black
Certification	CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014
Processor	
Built-in processor	Yes
Power	
Power consumption (max)	25.5 W
Power consumption (typical)	10 W
Output current	1.22 A
Output voltage	53 V
Total Power over Ethernet (PoE) budget	72 W
System requirements	
Mobile operating systems supported	Android, iOS
Browser supported	Chrome; IE; Safari; Edge; Firefox
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 93%
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	260 mm
Depth	232.5 mm
Height	47.6 mm
Weight	890 g
Package width	374 mm
Package depth	119 mm
Package height	311 mm

Package weight	2.05 kg
----------------	---------

Matmenys ir svoris

Matmenys (I × P × A)	29,00cm × 36,00cm × 9,00cm
----------------------	----------------------------

Svoris	1,00kg
--------	--------