

Dahua Technology Lite NVR4216-16P-EI network video recorder 1U Black

Gamintojas: **DAHUA** · Modelis: **NVR4216-16P-EI** · EAN: **6923172585790** · Prekės kodas: **716750**



439,90 €

Kaina su PVM

Be PVM: **363,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format
- ✓ Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled)
- ✓ Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding
- ✓ AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus
- ✓ AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map
- ✓ Connected to the third-party network cameras
- ✓ Security baseline 2.3



Aprašymas

This network video recorder features a 1U rack-mountable design and supports up to 16 channels, making it suitable for medium-scale surveillance setups. It is equipped with 16 Power over Ethernet (PoE) ports, which simplify the installation process by allowing both power and data to be transmitted over a single network cable. The device accommodates two hard drives, enhancing storage capacity for video recordings.

Equipped with WizSense technology, the recorder utilizes advanced artificial intelligence algorithms to offer improved object recognition and event

detection. This technology ensures more accurate alerts and reduces false alarms by distinguishing between human and vehicular shapes within the video feed.

The unit supports H.265 and H.264 video compression formats, optimizing storage efficiency without compromising video quality. It also features simultaneous HDMI and VGA video output, allowing users to connect multiple monitors for enhanced viewing and monitoring capabilities.

Remote access is facilitated through a compatible software application, enabling users to view live feeds and playback recorded footage from anywhere, provided there is internet connectivity. This feature ensures that monitoring can be managed remotely, adding an extra layer of convenience for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Video input channels	16 channels
Maximum resolution	1920 x 1080 pixels
Alarm input channels	4
Alarm output channels	2
Supported resolutions	1920x1080, 1280x1024, 1280x720, 1024x768
Bit rate	8192 Kbit/s
Number of users	128 user(s)
Two-way talk	Yes
Video motion detection	Yes
Number of motion detection zones	396
Video loss detection	Yes
On Screen Display (OSD)	Yes
Video formats supported	H.264, M-JPEG
Operating system installed	Embedded LINUX
Backup function	Yes
Split screen	Yes
PTZ control	Yes
Snapshot	Yes
Playback modes	Backup selection, Digital zoom, Forward, Full screen, Next camera, Pause, Play, Previous camera, Repeat, Reverse, Shuffle, Speed Adjust, Stop
Playback controls	Yes
Recording modes	Manual, Schedule, Stop
Recording time	120 min
Hard drive	

Maximum storage capacity	16 TB
Number of HDDs supported	2
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE) ports quantity	16
HDMI output	Yes
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Audio RCA inputs	1
Audio RCA outputs	1
Internal SATA ports quantity	2
RS-232 interface	Yes
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Features	
Rack mounting	Yes
Rack capacity	1U
Brand compatibility	Any brand
Product colour	Black
Processor	
Built-in processor	Yes
Processor cores	2
Power	
Power consumption (typical)	30 W
AC input voltage	100 - 240 V
AC input frequency	47/63 Hz
Power over Ethernet (PoE) power per port	25.5 W
Total Power over Ethernet (PoE) budget	130 W
System requirements	
Mobile operating systems supported	Android, iOS

Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 93%
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	375 mm
Depth	329.3 mm
Height	53 mm
Weight	2.6 kg
Package width	451 mm
Package depth	425 mm
Package height	147 mm
Package weight	3.8 kg
Matmenys ir svoris	
Matmenys (l × p × A)	43,00cm × 45,00cm × 15,00cm
Svoris	3,90kg