

Dahua Technology Lite NVR4232-4KS3 network video recorder 1U Black

Gamintojas: **DAHUA** · Modelis: **NVR4232-4KS3** · EAN: **6923172569370** · Prekės kodas: **716755**



245,90 €

Kaina su PVM

Be PVM: **203,22 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats
- ✓ Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps
- ✓ Max. 160/128/60 Mbps incoming/recording/outgoing bandwidth
- ✓ Supports IP cameras with a resolution up to 12 MP
- ✓ AI by Recorder supports 2-channel SMD Plus
- ✓ AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map
- ✓ Supports EPTZ, and one-click arming and disarming



Aprašymas

The **Dahua NVR4232-4KS3** is an advanced **Lite Network Video Recorder** designed to meet the demanding requirements of modern security systems. This **32-channel** NVR features **dual HDD support** and is optimized for high-resolution IP cameras, offering support for resolutions up to **12 MP**. With a maximum decoding capability of **8 × 1080p@30 fps** or **2 × 8 MP@30 fps**, it ensures smooth and clear video playback, making it suitable for a variety of monitoring applications.

The Dahua NVR4232-4KS3 utilizes state-of-the-art **Smart H.265+ and H.264** decoding formats, significantly enhancing video compression efficiency without sacrificing quality. With an incoming, recording, and outgoing bandwidth of up to **160/128/60 Mbps** respectively, this recorder can handle multiple high-definition streams simultaneously. Furthermore, its **AI capabilities** support advanced features such as face detection and

recognition, perimeter protection, and stereo analysis, providing users with cutting-edge security solutions.

Ideal for comprehensive surveillance setups, the Dahua NVR4232-4KS3's **AI by Recorder** functionality offers features like **2-channel SMD Plus** for intelligent motion detection, while **EPTZ** simplifies camera control with one-click arming and disarming options. Choose the Dahua NVR4232-4KS3 for unparalleled performance and reliability in video recording and monitoring.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Video input channels	32 channels
Maximum resolution	1920 x 1080 pixels
Alarm input channels	4
Supported resolutions	1920 x 1080 1280 x 1024 1280 x 720 1024 x 768
Bit rate	20000 Kbit/s
Number of users	128 user(s)
Two-way talk	Yes
Video motion detection	Yes
Number of motion detection zones	396
Video loss detection	Yes
Multi-screen	Yes
On Screen Display (OSD)	Yes
Video formats supported	H.264, H.264+, M-JPEG
Operating system installed	Embedded LINUX
Backup function	Yes
PTZ control	Yes
Playback modes	Backup selection, Digital zoom, Forward, Next camera, Pause, Play, Previous camera, Repeat, Shuffle, Stop
Playback controls	Yes
Recording modes	Manual, Schedule
Recording time	60 min
Hard drive	
Number of HDDs installed	0
HDD capacity	0 GB
Maximum storage capacity	6 TB
Number of HDDs supported	2

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	No
Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Internal SATA ports quantity	2
RS-485 ports	1
RS-232 interface	Yes
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support Dahua IP camera, DVR, NVS

Features

Rack mounting	Yes
Rack capacity	1U
Product colour	Black
Certification	CE, FCC, UL

Processor

Built-in processor	Yes
Processor cores	2

Power

Power consumption (typical)	10 W
Output current	4 A
Output voltage	12 V

System requirements

Mobile operating systems supported	Android
------------------------------------	---------

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 93%
Storage temperature (T-T)	-20 - 60 °C

Weight & dimensions

Width	375 mm
-------	--------

Depth	283 mm
Height	53 mm
Weight	1.49 kg
Package width	433 mm
Package depth	141 mm
Package height	366 mm
Package weight	2.77 kg
Matmenys ir svoris	
Matmenys (l × P × A)	36,00cm × 43,00cm × 14,00cm
Svoris	2,73kg