

Dahua Technology Lite HAC-HDW1200TRQ(-A) Turret CCTV security camera Indoor & outdoor 1920 x 1080 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **HAC-HDW1200TRQ-0280B-S6** · EAN: **6939554995729** · Prekės kodas: **716756**



20,90 €

Kaina su PVM

Be PVM: **17,27 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Max 30fps@1080P
- ✓ Quick-to-install eyeball saves installation time
- ✓ Built-in mic (-A)
- ✓ CVI/CVBS/AHD/TVI switchable
- ✓ 3.6mm fixed lens (2.8mm optional)
- ✓ Max. IR length 25m, Smart IR
- ✓ IP50, DC12V



Aprašymas

Equipped with a 2MP sensor, this HDCVI camera delivers high-definition video footage with a resolution of 1920 x 1080 pixels, ensuring clear and detailed images. The camera features a fixed-focal lens with a 2.8mm focal length, providing a wide-angle view suitable for comprehensive surveillance coverage.

Designed for both indoor and outdoor use, the camera is housed in a durable casing that is rated IP67, making it resistant to dust and water. It also includes infrared capabilities with a range of up to 20 meters, allowing for effective night vision.

The model supports multiple video formats including HDCVI, CVBS, AHD, and TVI, offering versatility and ease of integration with existing surveillance systems. Additionally, the camera incorporates advanced image processing technologies such as backlight compensation, automatic

white balance, and digital noise reduction to enhance image quality under varying lighting conditions.

This camera operates within a power supply range of 12V DC, making it energy efficient. Its compact design and adjustable mounting options facilitate easy installation in a variety of settings.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	CCTV security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Day/night mode	Yes
Certification	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Form factor	Turret
Housing material	Plastic
International Protection (IP) code	IP50
Camera	
Minimum illumination	0.02 lx
Angle of rotation	360°
Tilt angle range	0 - 78°
Pan range	0 - 360°
White balance	Auto, Manual
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Number of effective pixels (H x V)	1920 x 1080 pixels
Lens system	
Maximum aperture number	1.9
Fixed focal length	2.8 mm

Night vision

Night vision	Yes
Night vision distance	25 m
LED type	IR
Number of illumination LEDs	2

Video

Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Noise reduction	Yes
Noise reduction technology	2D noise reduction
Gain control type	Auto/Manual
Privacy masking	Yes
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Smart IR	Yes

Audio

Signal-to-Noise Ratio (SNR)	65 dB
Built-in microphone	Yes

Storage

Built-in HDD	No
--------------	----

Security

Mirror	Yes
--------	-----

Power

Power source type	DC
Power consumption (max)	2.6 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Depth	93 mm
-------	-------

Height	97.1 mm
--------	---------

Weight	170 g
--------	-------

Packaging data

Package weight	230 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (l × P × A)	12,00cm × 13,00cm × 11,00cm
----------------------	-----------------------------

Svoris	0,30kg
--------	--------