

Dahua Technology DH-LR2110-8ET-120 L2 Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Gamintojas: **DAHUA** · Modelis: **LR2110-8ET-120-V2** · EAN: **6923172594099** · Prekės kodas: **716776**



172,90 €

Kaina su PVM

Be PVM: **142,89 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports long distance PoE transmission up to 800m with ePoE technology of Dahua
- ✓ Layer-two ePoE switch· MAC auto study and aging, MAC address list capacity is 8K
- ✓ Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- ✓ Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard
- ✓ Industrial wide temperature design
- ✓ Port indicator light is to display the status of current transmission mode for the port, which includes IEEE, E100 and E10

Aprašymas

DH-LR2110-8ET-120 is a 8-Port ePoE switch, which is able to realize PoE transmission over 800 meters Ethernet cable at the speed of 10Mbps, or 300 meters at the speed of 100Mbps. Besides, it supports PoE and PoC power supply technology, which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

Techninė specifikacija

Specifications

Sandėlio grupė

Networking [+782][-3085]

Management features

Switch layer

L2

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Fast Ethernet (copper) ports quantity	8
Gigabit Ethernet (copper) ports quantity	1
SFP module slots quantity	1

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Flow control support	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	8.8 Gbit/s
Forwarding rate	4.17 Mpps
Packet buffer memory	2.75 MB

Design

Product colour	Black
LED indicators	Yes

Power

Power supply included	Yes
DC input voltage	48 - 57 V

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	120 W

Operational conditions

Operating temperature (T-T)	-30 - 65 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	150 mm
Depth	100 mm
Height	42 mm
Weight	590 g

Matmenys ir svoris

Matmenys (I × P × A)	24,00cm × 27,00cm × 8,00cm
Svoris	1,50kg