

Dahua PFM976-631-PT

Gamintojas: DAHUA · Modelis: PFM976-631-PT · Prekės kodas: 716778

12,90 €

Kaina su PVM

Be PVM: 10,66 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

HIGH-PERFORMANCE UTP CAT6 CABLE FOR RELIABLE CONNECTIVITY

The UTP CAT6 15U cable by Dahua is engineered for optimal performance in high-speed networking applications. With a robust construction that includes a combination of PC and brass materials, this cable ensures durability and longevity. The gold plating thickness of 15U enhances conductivity, minimizing contact resistance to $\leq 20\text{ m}\Omega$, which is crucial for maintaining signal integrity over extended distances. Designed to operate at a voltage of 150 VAC RMS and a current of 1.5 AMP, this cable is perfect for both residential and commercial installations.

EXCEPTIONAL DURABILITY AND ENVIRONMENTAL RESISTANCE

This UTP CAT6 cable boasts a flammability rating of UL94V-2, ensuring safety in various environments. It is built to withstand extreme conditions, with an operating temperature range of $-25\text{ }^{\circ}\text{C}$ to $+55\text{ }^{\circ}\text{C}$ ($-13\text{ }^{\circ}\text{F}$ to $+131\text{ }^{\circ}\text{F}$) and a storage temperature of $-10\text{ }^{\circ}\text{C}$ to $+40\text{ }^{\circ}\text{C}$ ($+14\text{ }^{\circ}\text{F}$ to $+104\text{ }^{\circ}\text{F}$). The cable's insulation resistance exceeds 1000 M Ω at 500 VDC, providing excellent protection against electrical interference. With a lifespan of up to 750 insertions and a retention strength of 50 N for 60 seconds, this cable is designed for repeated use without compromising performance.

COMPACT AND EFFICIENT PACKAGING FOR EASY HANDLING

The UTP CAT6 15U cable is packaged efficiently to facilitate easy transport and storage. Each carton contains 100 pieces, with 50 cartons per transport package, making it ideal for bulk purchases. The compact dimensions of the packaging (120 mm $\times$ 65 mm $\times$ 90 mm) ensure that it occupies minimal space, while the net weight of 0.14 kg (0.31 lb) per unit makes it lightweight for handling. This thoughtful packaging design not only protects the cables during transit but also simplifies inventory management for distributors and retailers.

Techninė specifikacija

Specifications

Sandėlio grupė

without Category [+99][-2182]