

ATEN 0U Basic PDU with Surge Protection

Gamintojas: **ATEN** · Modelis: **PE0224SG-AT-G** · EAN: **4719264649066** · Prekės kodas: **716927**

PE0224SG



172,90 €

Kaina su PVM

Be PVM: **142,89 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Space saving – 0U rack mount design
- ✓ IEC or NEMA outlet models
- ✓ Overcurrent protection
- ✓ Surge protection
- ✓ Aluminum material
- ✓ Works with data centers, server rooms, and telecom equipment



Note: (1) No items are shown. Basic PDU, PE0224SG Basic and PE0224SG Outlet are the standard 3U and 1U rackmount units.

Aprašymas

ATEN's Basic PDU family is extended with 0U members containing 24 outlets and available in IEC or NEMA socket configurations. The compact aluminum housing gives a sleek, yet robust look while minimizing installation space for work space efficiency. Thanks to the built-in surge protection module, the IT devices connected to the PDU are well-protected from sudden surges in electricity; plus, the equipment downtime is reduced as a result of the overcurrent protection design. The Basic PDUs are tailored made for individuals who are in need of industrial-grade, easy-to-deploy power distribution unit in data centers, server rooms, and network wiring closets.

- 1 x power distribution unit
- 1 x power cord
- 1 x L-shaped mounting kit
- 1 x user instructions

Techninė specifikacija

Specifications

Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
----------------	--

Design

PDU types	Basic
Rack capacity	0U
Housing material	Aluminium
Product colour	Black

Ports & interfaces

AC outlets quantity	24 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 320

Features

Cable length	3.048 m
--------------	---------

Power

Nominal input voltage	100-240 V
Maximum current	16 A
AC input frequency	50-60 Hz
Block 1 output current	10 A
Block 2 output current	16 A
Load capacity	3840 VA
Maximum input current per phase	16 A
Surge protection	Yes

Certificates

Certification	CE
---------------	----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m

Weight & dimensions

Width	44.4 mm
Depth	966.8 mm
Height	60 mm
Weight	2.05 kg

Packaging content

Cables included	AC
-----------------	----

Packaging data

Package weight	2.81 kg
Package width	145 mm
Package depth	1177 mm
Package height	166 mm

Logistics data

Master (outer) case net weight	2.05 kg
Master (outer) case width	146 mm
Master (outer) case length	1177 mm
Master (outer) case height	166 mm
Master (outer) case gross weight	2.81 kg
Products per master (outer) case	1 pc(s)

Matmenys ir svoris

Matmenys (I × P × A)	97,00cm × 4,00cm × 6,00cm
Svoris	2,91kg