

TP-Link Omada EAP650-DESKTOP wireless access point 2976 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP650-Desktop** · EAN: **1210002605939** · Prekės kodas: **717086**



147,90 €

Kaina su PVM

Be PVM: **122,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Blazing-Fast AX3000 WiFi 6 Speeds: 574 Mbps on 2.4 GHz and 2402 Mbps on 5GHz totals 2976 Mbps WiFi speeds. †
- ✓ Multiple Gigabit Ports: Connect multiple devices with 4× Gigabit Ethernet Ports
- ✓ Convenient Deployment: Supports both 802.3bt PoE++ and DC (adapter included) for easy and quick deployment
- ✓ No Installation needed: Supports desktop installation without the need for additional setup
- ✓ High Flexibility: Provide flexible installation solutions for both desktop and wall mounting
- ✓ Stay Smooth with Seamless Roaming: Users can enjoy seamless streaming across the property with their devices switching effortlessly between access points.§
- ✓ Centralized Cloud Management: Integrates with the Omada SDN platform for Centralized Management. §



Aprašymas

TP-Link Omada EAP650-DESKTOP. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2976 Mbit/s. Security algorithms: 802.1x RADIUS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise,.... Ethernet LAN data rates: 1000 Mbit/s. Power over Ethernet (PoE). Product color: White. Power consumption (max): 17.3 W

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	2976 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	2402 Mbit/s
Ethernet LAN data rates	1000 Mbit/s
Networking standards	IEEE 802.3af, IEEE 802.3bt
Channel bandwidth	160 MHz
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Rate limiting	Yes
Load balancing	Yes
Band steering	Yes
Airtime Fairness (ATF)	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	20 - 29 dBm
Transmitting power (FCC)	26 - 27 dBm
Security	
Security algorithms	802.1x RADIUS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	16
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Management platform	Omada

Ports & interfaces

Ethernet LAN (RJ-45) ports	4
----------------------------	---

Power

Power over Ethernet (PoE)	Yes
DC voltage range	12 V
Input current	1.5 A
Power consumption (max)	17.3 W

Design

Placement	Table
Product colour	White
Reset button	Yes
LED indicators	Yes

Antenna

Antenna type	Internal
Antenna gain level (max)	4.7 dBi

Performance

Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
------------------------------	--

Certificates

Certification	CE, FCC, RoHS, IC
---------------	-------------------

Weight & dimensions

Width	140 mm
Depth	33 mm
Height	175 mm
Weight	452 g

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%

Other features

Wireless standard	IEEE 802.11 a/b/g/n/ac/ax
-------------------	---------------------------

Matmenys ir svoris

Matmenys (l × p × A)18,00cm × 21,00cm × 10,00cm

Svoris1,00kg