

Dahua Technology WizSense IPC-HFW3849T1-AS-PV Bullet IP security camera Outdoor 3840 x 2160 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **IPC-HFW3849T1-AS-PV-0280B-S5** · EAN: **6923172525512** · Prekės kodas: **717243**



214,90 €

Kaina su PVM

Be PVM: **177,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8MP, 1/2.8" CMOS image sensor, low illuminance, high image definition
- ✓ Outputs max. 8MP (3840 × 2160) @20 fps (AI function enabled by default) and supports 8MP (3840 × 2160) @25/30 fps (with AI function disabled)
- ✓ H.265 codec, high compression rate, low bit rate
- ✓ Built-in warm illuminator, and the max. illumination distance: 30 m
- ✓ ROI, SMART H.264+/H.265+, flexible coding, applicable to various band width and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent detection: Tripwire, intrusion (the three functions support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, net work disconnection, IP conflict, illegal access, and voltage detection
- ✓ Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing
- ✓ Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period



Aprašymas

8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes
Certification	CE-LVD: EN62368-1 CE-EMC: 2014/30/EU FCC: 47 CFR FCC 15, B
Design	
Mounting type	Ceiling/wall
Product colour	White
Form factor	Bullet
Housing material	Metal, Plastic
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.007 lx
Angle of rotation	360°
Lens viewing angle, horizontal	107°
Lens viewing angle, vertical	56°
Lens viewing angle, diagonal	127°
Tilt angle range	0 - 90°
Pan range	0 - 360°
White balance	Auto, Manual, Natural, Outdoor
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")

Progressive scan	Yes
Lens system	
Number of lenses	1
Maximum aperture number	1.4
Fixed focal length	2.8 mm
Detect distance (wide)	87.7 m
Detect distance (tele)	110.3 m
Observe distance (wide)	35.1 m
Observe distance (tele)	44.1 m
Recognize distance (wide)	17.5 m
Recognize distance (tele)	22.1 m
Identify distance (wide)	8.8 m
Identify distance (tele)	11 m
Closest focusing distance	1.5 m
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2592 x 1944, 2688 x 1520, 3072 x 1728, 3072 x 2048, 3840 x 2160
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	3 kbps-8192 kbps
Back Light Compensation (BLC)	Yes

Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Built-in microphone	Yes
Voice codecs	G.711Mu, G.711a, G.726, PCM
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.1x, IEEE 802.3af
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA ; PPPoE; SNMP
Number of users	20 user(s)
Quality of Service (QoS) support	Yes
Streaming method	Multicast
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	512 MB
ROM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Video motion detection	Yes
IP address filtering	Yes
Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Mirror	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	8.2 W

Power consumption (Power over Ethernet (PoE))	9.7 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	94.4 mm
Depth	84.7 mm
Length	288.4 mm
Weight	1 kg
Packaging data	
Package weight	1.23 kg
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (I × P × A)	15,00cm × 34,00cm × 14,00cm
Svoris	1,30kg