

Dahua Technology SD4A425DB-HNY Spherical IP security camera Indoor & outdoor 3860 x 2160 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **SD4A425DB-HNY** · EAN: **6923169706207** · Prekės kodas: **717246**



475,91 €

Kaina su PVM

Be PVM: **393,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/2.8" 4Megapixel STARVIS™ CMOS
- ✓ 25x optical zoom
- ✓ Starlight technology
- ✓ Max. 25/30fps@4MP
- ✓ IR distance up to 100 m
- ✓ Auto-tracking 1.0
- ✓ Perimeter protection
- ✓ Face detection
- ✓ SMD 3.0
- ✓ IP66



Aprašymas

With its powerful optical zoom, and accurate pan and tilt capabilities, the PTZ camera provides an all-in-one solution for long distance video surveillance of outdoor scenes. Together with infrared illumination and Starlight Technology, the camera is a great solution for dark, low light conditions. The series combines a day and night mechanical IR cut filter to produce high quality images in variable lighting conditions during the day.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Auto-tracking	Yes
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes
Built-in light	Yes
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Spherical
International Protection (IP) code	IP66
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.0005 lx
Lens viewing angle, horizontal	51.9°
Lens viewing angle, vertical	39.7°
Lens viewing angle, diagonal	63.1°
Tilt angle range	-5 - 90°
Tilt preset speed	160 °/sec
Tilt manual speed	0.1 - 160 °/sec
Pan range	0 - 360°
Pan preset speed	240 °/sec
Pan manual speed	0.1 - 240 °/sec
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Sodium lamp, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1 - 1/30000 s
Number of Privacy masking areas	24
Image sensor	

Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Progressive scan	Yes
Lens system	
Number of lenses	1
Detect distance	2500 m
Observe distance	987.5 m
Recognize distance	500 m
Focal length range	5 - 125 mm
Auto focus	Yes
Focus	Motorized
Identify distance	250 m
Night vision	
Night vision	Yes
Night vision distance	100 m
LED type	IR
Number of illumination LEDs	6
Video	
Maximum resolution	3860 x 2160 pixels
Total megapixels	4 MP
Video formats supported	H.264+, H.265+
Frame rate	25 fps
Audio	
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Built-in microphone	Yes
Voice codecs	PCM, G.711a, G.711Mu, G.726, G.723
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet
Supported network protocols	ARP, Bonjour, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NFS, NTP, PPPoE, QoS, RTCP, RTMP, RTP, RTSP, SAMBA, SMTP, SNMP, SSL, TCP/ IP, UDP, UPnP, 802.1X
Number of users	20 user(s)
Streaming method	Multicast, Unicast

Live view	Yes
Storage	
Built-in HDD	No
ROM capacity	128 MB
RAM capacity	512 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Alarm input channels	2
Alarm output channels	1
Siren noise level	55 dB
Management features	
Cloud-managed	Yes
Web-based management	Yes
Power	
Power source type	DC, PoE
Power consumption (typical)	9.5 W
Power consumption (Power over Ethernet (PoE))	21.5 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 65 °C
Weight & dimensions	
Height	170.4 mm
Diameter	17.1 cm
Weight	2.5 kg
Packaging data	
Package weight	3.2 kg
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (I × P × A)	21,00cm × 22,00cm × 28,00cm
Svoris	3,20kg