

Dahua Technology DH-F4C-PV security camera Bullet IP security camera Indoor & outdoor 2560 x 1440 pixels Wall

Gamintojas: **DAHUA** · Modelis: **F4C-PV** · EAN: **6939554914522** · Prekės kodas: **717247**



48,90 €

Kaina su PVM

Be PVM: **40,41 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ · 4-MP 1/3" CMOS image sensor, low luminance, and high definition image
- ✓ · Outputs max. 4 MP (2560 ×1440)@25/30 fps
- ✓ · H.265 codec, high compression rate, ultra-low bit rate
- ✓ · Built-in warm light and IR LED, and the max. illumination distance is 30 m
- ✓ · SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- ✓ · DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes

Aprašymas

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/ residences, small-sized retail stores, and other small and medium-sized enterprises.

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Day/Night

Dahua Day/Night function provides color image when illumination is adequate; when illuminance is inadequate, it switches night mode and provides white and black image. It can guarantee that the network camera can work normally when illuminance changes.

Two-way Talk

With its built-in high-sensitivity microphone and high-power speaker, the camera realizes two-way talk through the mobile app.

Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the white light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the white light is off and the IR illuminator is on, which reduces light pollution efficiently.

Techninė specifikacija

Specifications	
Sandėlio grupė	Surveillance Systems [+315][-2956]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired & Wireless
Day/night mode	Yes
Design	
Mounting type	Wall
Product colour	Black, White
Form factor	Bullet
Housing material	Metal, Plastic
International Protection (IP) code	IP67
Camera	
Minimum illumination	0.0005 lx
Tilt angle range	-60 - 40°
Pan range	0 - 360°
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp
Camera shutter speed	1/3 -1/100000
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 3 mm (1 / 3")
Lens system	
Number of lenses	1
Maximum aperture number	1.6
Night vision	
Night vision	Yes

Night vision distance	30 m
LED type	IR/White
Number of illumination LEDs	4
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264B, H.264H, H.265
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Region of Interest (ROI) encoding	Yes
Audio	
Built-in speaker(s)	Yes
Audio formats supported	G.711 A-law, G.726, PCM
Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	IPv4; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; DHCP; DNS; NTP; Multicast; RTMP; P2P
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Number of users	20 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB

ROM capacity	16 MB
RAM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Video motion detection	Yes
Mirror	Yes
Power	
Power source type	DC
Power consumption (typical)	2.2 W
Power consumption (max)	6.6 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-30 - 60 °C
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Width	78.4 mm
Depth	131 mm
Height	97.2 mm
Weight	254.5 g
Packaging data	
Package weight	503 g
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (I × P × A)	11,00cm × 22,00cm × 11,00cm
Svoris	0,60kg