

TP-Link EAP725-Wall 5012 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP725-Wall** · EAN: **8885020626353** · Prekės kodas: **717273**



175,90 €

Kaina su PVM

Be PVM: **145,37 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ BE3600 Wi-Fi 7 (2882 Mbps on 5 GHz + 688 Mbps on 2.4 GHz)
- ✓ 1x 2.5G PoE input port + 1x 2.5G pass-through port + 2x Gigabit RJ45 downlink ports
- ✓ 160 MHz bandwidth enables many more simultaneous transmissions
- ✓ Multi-RUs ensure the high performance of your network
- ✓ Advanced Functions: Centralized management, Mesh, and Seamless Roaming



Aprašymas

BE3600 WiFi 7 Wall Plate Access Point for Ultra-Fast Connectivity

Optimized Wired Performance with 2.5G PoE Ports

With 2.5G PoE input and pass-through ports, along with two Gigabit RJ45 ports, enjoy high-speed data transfers and connect multiple devices to your gigabit network. Wired devices, such as IP Phones, can be powered without the need for additional electrical cables.

Seamless Integration into the Omada SDN

Remotely manage your access points, switches, and routers across multiple sites — all from a single interface.

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	5012 Mbit/s
Maximum data transfer rate (2.4 GHz)	688 Mbit/s
Maximum data transfer rate (5 GHz)	2882 Mbit/s
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at
Number of users	250 user(s)
VLAN support	Yes
Airtime Fairness (ATF)	Yes
BeamForming	Yes
Security	
Security algorithms	WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
MAC address filtering	Yes
Number of SSID supported	16
Remote Authentication Dial-In User Service (RADIUS)	Yes
Access Control List (ACL)	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	3
Power	
Power over Ethernet (PoE)	Yes
Power consumption (max)	17 W
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes

LED indicators	Yes
Antenna	
Antenna type	Internal
Antennas quantity	4
Antenna gain level (max)	5 dBi
Performance	
Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux
Certificates	
Certification	FCC, RoHS
Weight & dimensions	
Width	86 mm
Depth	40 mm
Height	143 mm
Packaging data	
Package type	Box
Packaging content	
Quantity per pack	1 pc(s)
Mounting kit	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Matmenys ir svoris	
Matmenys (I × P × A)	6,00cm × 12,00cm × 19,00cm
Svoris	0,49kg