

Ubiquiti UPS-2U 2U Rack UPS Power Supply

Gamintojas: **UBIQUITI** · Modelis: **UPS-2U** · EAN: **810177161875** · Prekės kodas: **717445**



458,90 €

Kaina su PVM

Be PVM: 379,26 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

RELIABLE POWER BACKUP FOR CRITICAL SYSTEMS

The UniFi UPS 2U is a robust uninterruptible power supply designed to ensure that critical systems remain operational during power outages. With a capacity of 1,500VA and 1,000W, this managed rackmount UPS provides reliable backup power through its four battery backup outlets and four surge protection outlets. Its half-load runtime of 8 minutes allows for graceful shutdowns of connected devices, such as UNVR and UNAS, safeguarding data and preventing unexpected downtime.

DURABLE DESIGN AND EFFICIENT MANAGEMENT FEATURES

Constructed from galvanized steel, the UniFi UPS 2U is built to withstand the rigors of a data center environment. Its 2U rackmount form factor makes it easy to integrate into existing server racks. The UPS features an Ethernet management interface, allowing for seamless network connectivity and monitoring. With NUT compatibility, it can also support third-party devices, enhancing its versatility in various setups. The device is designed for easy maintenance, featuring a field-replaceable battery that ensures minimal disruption during battery changes.

ADVANCED PROTECTION AND PERFORMANCE SPECIFICATIONS

This UPS is equipped with advanced features to protect connected devices from power anomalies. It operates within an input voltage range of 170–280V AC and provides output voltage regulation of $\pm 10\%$ in battery mode. The simulated sine wave output ensures compatibility with a wide range of electronic equipment. With a transfer time of just 6 ms, the UniFi UPS 2U minimizes the risk of disruption during power transitions. Additionally, it includes overload and short circuit protection, ensuring safe operation under various conditions.

VERSATILE OPERATING CONDITIONS AND CERTIFICATIONS

The UniFi UPS 2U is designed to perform reliably in diverse environments, with an operating temperature range of 0 to 40°C and humidity tolerance of 0 to 95% noncondensing. It can operate effectively at altitudes up to 3,000 meters, making it suitable for various installations. The unit is certified to CE and IEC 62040-1 standards, ensuring compliance with international safety and performance regulations. This combination of versatility and certification makes the UniFi UPS 2U an ideal choice for businesses seeking dependable power solutions.

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	58,00cm × 26,00cm × 56,00cm
Svoris	18,00kg