

CyberPower CP1600EPFCLCD uninterruptible power supply (UPS) Line-Interactive 1.6 kVA 1000 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **CP1600EPFCLCD** · EAN: **4711027798615** · Prekės kodas: **717459**



390,90 €

Kaina su PVM

Be PVM: **323,06 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 1.6 kVA 1000 W
- ✓ Waveform: Pure sine
- ✓ 6 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Tower Black



Aprašymas

CyberPower CP1600EPFCLCD with Pure Sine Wave output safeguards mid- to high-end computer systems, servers and networking hardware that use conventional and Active Power Factor Correction (PFC) power supplies. Designed with GreenPower UPS™ Technology to improve UPS operating efficiency and to minimize its energy consumption, this UPS delivers significant energy cost savings over conventional UPS systems.

The UPS provides Automatic Voltage Regulation (AVR) to maintain stable voltage for connected equipment. The product features data line protection with high-speed transmission to safeguard communication equipment against surges/spikes as well as supply 1Gbps speed to transmit data. With tiltable color LCD panel, users can monitor key power and battery information at a glance. The PowerPanel Power Management Software allows user to perform real-time monitoring and configuration.

Techninė specifikacija

Specifications	
Sandėlio grupė	Batteries & Power Supplies [+210][-1232]
Features	
UPS topology	Line-Interactive
Output power capacity	1.6 kVA
Output power	1000 W
Waveform	Pure sine
Input operation voltage (min)	169 V
Input operation voltage (max)	271 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
Surge energy rating	405 J
Response time	8 ms
Heat dissipation	24 BTU/h
Power Factor Correction (PFC) type	Active
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Socket circuit breaker	Yes
Ports & interfaces	
AC outlet types	Type F
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	2
USB port type	USB Type A/USB Type-C

Serial interface	Yes
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	2.6 min
Typical backup time at half load	9.7 min
Battery recharge time	8 h
Replacement battery cartridge	RBP0142
Design	
Form factor	Tower
Product colour	Black
Cable length	1.83 m
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Batteries included	Yes
Quick installation guide	Yes
Weight & dimensions	
Width	100 mm
Depth	355 mm
Height	280 mm
Weight	11 kg

Packaging data	
Package width	195 mm
Package depth	466 mm
Package height	370 mm
Package weight	13 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Other features	
Nominal output voltage	230 V
Nominal input voltage	220-240 V
Overload protection	Yes
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	39,00cm × 45,00cm × 19,00cm
Svoris	12,10kg