

TP-Link Omada 10-Port Gigabit Industrial Easy Managed Switch with 6-Port PoE+ and 2-Port PoE++

Gamintojas: **TP-LINK** · Modelis: **IES210GPP** · EAN: **1210002602112** · Prekės kodas: **717526**



292,90 €

Kaina su PVM

Be PVM: **242,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6x 10/100/1000Mbps RJ45 ports (4x 802.3af/at-compliant PoE+)
- ✓ 65W Power Budget, with up to 30W for each PoE port
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralised Cloud Management via the web or the Omada app
- ✓ Up to 250m PoE, QoS, PoE Auto Recovery, and Port Isolation for reliable surveillance networking
- ✓ Automatic Loop Prevention, VLAN, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

Omada Industrial 10-Port Gigabit Easy Managed PoE++ Switch

Industrial-Grade Protection Built for Harsh Environments

- 10x Gigabit Ports (2x PoE++, 6x PoE+, 2x RJ45/SFP Combo)
- 240W Total PoE Budget

- 40°C to 75°C Operating Temperature
- 12~57VDC 1+1 Redundant Power Input
- Industrial-Grade IP40 Aluminum Casing
- Abundant Functions for CCTV Networking
- Easy Centralised Management
- DIN-Rail & Wall Mounting

Techninė specifikacija

Specifications	
Sandėlio grupė	Networking [+782][-3085]
Management features	
Switch type	Managed
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Combo SFP ports quantity	2
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
VLAN support	Yes
Number of VLANs	4000
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Store-and-forward	Yes

Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	4000 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Form factor	DIN rail
Product colour	Grey
LED indicators	Yes
Power	
Power source	DC
DC input voltage	12 - 57 V
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	6
Power over Ethernet 4PPoE (PoE++) ports quantity	2
Total Power over Ethernet (PoE) budget	240 W
Weight & dimensions	
Width	155 mm
Depth	120 mm
Height	60 mm
Matmenys ir svoris	
Matmenys (I × P × A)	19,00cm × 20,00cm × 10,00cm
Svoris	1,56kg