

TP-Link Omada 5-Port Gigabit Easy Managed Switch

 Gamintojas: **TP-LINK** · Modelis: **ES205G** · EAN: **8885020620924** · Prekės kodas: **717651**


31,90 €

Kaina su PVM

 Be PVM: **26,36 €**


Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5x 10/100/1000Mbps RJ45 ports
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralised Cloud Management via the web or the Omada app
- ✓ Automatic Loop Prevention, VLAN, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

Omada 5-Port Gigabit Easy Managed Switch

Software Defined Networking (SDN) with Cloud Access

Remotely manage your access points, switches, and gateways across multiple sites all from a single interface.

Compact and Durable Metal Casing, Featuring Desktop/Wall Mounting and a Fanless Design

Techninė specifikacija

Specifications

Sandėlio grupė Networking [+782][-3085]

Management features

Switch type Managed

Quality of Service (QoS) support Yes

Cloud-managed Yes

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity 5

Basic switching RJ-45 Ethernet ports type Gigabit Ethernet (10/100/1000)

Network

Networking standards IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3x

10G support No

Port mirroring Yes

Flow control support Yes

Link aggregation Yes

Auto MDI/MDI-X Yes

Auto-negotiation Yes

VLAN support Yes

Virtual LAN features MTU VLAN, Port-based VLAN, Tagged VLAN

Data transmission

MAC address table 8000 entries

Switching capacity 10 Gbit/s

Forwarding rate 7.4 Mpps

Store-and-forward Yes

Jumbo frames support Yes

Jumbo frames 15

Packet buffer memory 4 MB

Security

DHCP features DHCP client

IGMP snooping Yes

Loop protection Yes

Design

Product colour Black

Reset button Yes

LED indicators Yes

Wall mountable	Yes
Performance	
Fanless	Yes
Power	
Power source	AC/DC
Power supply included	Yes
DC input voltage	5 V
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	100 mm
Depth	98 mm
Height	25 mm
Packaging content	
User guide	Yes
Packaging data	
Package type	Box
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 10,00cm × 3,00cm
Svoris	4,80kg