

TP-Link Omada 10G Multi-Gigabit SFP Media Converter

Gamintojas: **TP-LINK** · Modelis: **MC420L** · EAN: **8885020625554** · Prekės kodas: **717665**



61,90 €

Kaina su PVM

Be PVM: **51,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1x 1G/2.5G/5G/10Gbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX
- ✓ Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
- ✓ Complies with IEEE 802.3an, IEEE 802.3ae, and IEEE 802.3aq
- ✓ FX port supports hot-swappable
- ✓ Maximum transmission distance depends on the inserting SFP

Aprašymas

What This Product Does

The MC420L is a media converter designed to convert between 10GBASE-SR/LR fiber, 10GBASE-LRM fiber and 10GBASE-T copper media. It easily extends the distance of an existing gigabit network via fiber optic when integrated with the SFP Module. The MC420L applies the IEEE 802.3ae 10GBASE-SR/LR 10G Ethernet & IEEE 802.3an 10GBASE-T 10G Ethernet standards as part of its intended use with multi-mode/single-mode SFP Module. Long-range point-to-point connections are easily built with the gigabit fiber converters, making them ideal for network connections across multiple buildings, for remote surveillance and automated factory equipment.

MC420L offers flexible installation on standalone desktops or inserted into a chassis (TP-Link's MC1400). The easy-to-view front panel status LEDs provide real-time status information to monitor up-to-the-minute network activity. While the maximum transmission distance of fiber optics depends on the insertion of the SFP module.

Techninė specifikacija

Specifications

Sandėlio grupė

Networking [+782][-3085]

Network

Maximum data transfer rate	10000 Mbit/s
Networking standards	IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3x, IEEE 802.3z
Copper ethernet cabling technology	2.5GBASE-T, 10GBASE-T, 1000BASE-T
Data transfer rate	10000 Mbit/s
Auto-negotiation	Yes
Duplex system	Full, Half
Performance	
Maximum transfer distance	100 m
Fiber mode structure	Multi-mode, Single-mode
Features	
Internal	No
LED indicators	Activity, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SFP+
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Power consumption (max)	4.12 W
Weight & dimensions	
Width	94.5 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging content	
AC adapter included	Yes
Manual	Yes
Certificates	
Compliance certificates	RoHS, UL

Matmenys ir svoris	
Matmenys (l × p × A)	17,00cm × 21,00cm × 7,00cm
Svoris	0,55kg