

DELL PowerEdge T160 server 480 GB Tower (3U) Intel Xeon 6 6325P 3.5 GHz 32 GB DDR5-SDRAM 300 W

Gamintojas: **DELL** · Modelis: **WYKPV** · EAN: **5397184970140** · Prekės kodas: **717690**



3 793,89 €

Kaina su PVM

Be PVM: **3 135,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6325P (12MB Cache, 3.5GHz)
- ✓ 32GB DDR5-SDRAM (1 x 32) & 480GB SSD
- ✓ iDRAC9, Enterprise 16G



Aprašymas

The single-socket Dell PowerEdge T160 is a small chassis tower server for customers desiring flexibility, affordability and processing power.

Techninė specifikacija

Specifications

Sandėlio grupė Computers [+193][-2216]

Processor

Processor family Intel Xeon 6

Processor manufacturer Intel

Processor model	6325P
Processor frequency	3.5 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	8
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz

Memory

Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	Yes
Memory layout (slots x size)	1 x 32 GB
Memory data transfer rate	5600 MT/s

Storage

Total storage capacity	480 GB
RAID support	No
Optical drive type	No
Number of SSDs installed	1
SSD capacity	480 GB
SSD interface	SATA III
SSD size	2.5"
Supported SSD sizes	2.5"
Number of SSDs supported	2
Supported RAID controllers	PERC H355 Adapter LP
Drive writes per day (DWPD)	1
Storage drive adapter included	Yes
Storage drive adapter type	2.5" - 3.5"

Network

LAN controller	Broadcom 5720
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Design	
Chassis type	Tower (3U)
Product colour	Black
Performance	
Remote administration	iDRAC9, Enterprise 16G
Software	
Operating system installed	No
Compatible operating systems	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Power	
Redundant power supply (RPS) support	No
Power supply	300 W
Number of main power supplies	1
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m
Carbon footprint	
Total carbon footprint (kg of CO2e)	1182
Total carbon emissions, standard deviation (kg of CO2e)	924
Carbon emissions, manufacturing (kg of CO2e)	319.14
Carbon emissions, logistics (kg of CO2e)	130.02
Carbon emissions, energy usage (kg of CO2e)	709.2

Carbon emissions, end-of-life (kg of CO2e)	23.64
--	-------

Weight & dimensions

Width	132.5 mm
-------	----------

Height	332.5 mm
--------	----------

Packaging content

Packaging content	European Power Cord 220V
-------------------	--------------------------

Other features

Data transfer rate	6 Gbit/s
--------------------	----------

Bytes per sector	512e
------------------	------

Target workload	Read Intensive (RI)
-----------------	---------------------

Matmenys ir svoris

Matmenys (l × P × A)	33,00cm × 98,00cm × 13,00cm
----------------------	-----------------------------

Svoris	11,10kg
--------	---------