

DELL PowerEdge R260 server 480 GB Rack (1U) Intel Xeon 6 6325P 3.5 GHz 16 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **EMEA_PROMO_R260_SPL2** · EAN: **5902002354684** · Prekės kodas: **717709**



3 791,90 €

Kaina su PVM

Be PVM: **3 133,80 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel Xeon 6 6325P 3.5 GHz
- ✓ 480 GB
- ✓ 16 GB DDR5-SDRAM
- ✓ Rack (1U) 700 W



Aprašymas

DELL PowerEdge R260. Processor family: Intel Xeon 6, Processor frequency: 3.5 GHz, Processor model: 6325P. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W. Chassis type: Rack (1U)

Techninė specifikacija

Specifications

Sandėlio grupė

Computers [+193][-2216]

Processor

Processor family	Intel Xeon 6
Processor manufacturer	Intel
Processor model	6325P
Processor frequency	3.5 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	8
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz
Memory	
Internal memory	16 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Memory slots	4x DIMM
Storage	
Total storage capacity	480 GB
RAID support	Yes
Optical drive type	No
Number of SSDs installed	1
SSD capacity	480 GB
SSD interface	SATA III
SSD size	2.5"
Supported SSD sizes	2.5"
Number of SSDs supported	6
Supported RAID controllers	PERC H355 Adapter LP
Hot-Plug support	Yes
Drive writes per day (DWPD)	3
Network	
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)

Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Design	
Chassis type	Rack (1U)
Product colour	Black
Rack rails	Yes
Performance	
Trusted Platform Module (TPM)	Yes
Software	
Operating system installed	No
Power	
Redundant power supply (RPS) support	No
Power supply	700 W
Number of main power supplies	1
Power supply input voltage	200 - 240 V
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m
Certificates	
80 PLUS certification	80 PLUS Titanium
Carbon footprint	
Total carbon footprint (kg of CO2e)	950
Total carbon emissions, standard deviation (kg of CO2e)	711
Carbon emissions, manufacturing (kg of CO2e)	304
Carbon emissions, logistics (kg of CO2e)	95
Carbon emissions, energy usage (kg of CO2e)	541.5
Carbon emissions, end-of-life (kg of CO2e)	9.5

PAIA version	PAIA 1.3.2, 2024
Weight & dimensions	
Width	482 mm
Height	42.8 mm
Packaging content	
Packaging content	Riser Config 1, Gen4 Riser
Other features	
Data transfer rate	6 Gbit/s
Bytes per sector	512e
Target workload	Read Intensive (RI)
Matmenys ir svoris	
Matmenys (l × p × A)	60,00cm × 78,00cm × 24,00cm
Svoris	14,00kg