

TP-Link Outdoor Pan/Tilt 4G LTE Camera

Gamintojas: **TP-LINK** · Modelis: **Tapo C501GW** · EAN: **8885020621037** · Prekės kodas: **717731**



98,91 €

Kaina su PVM

Be PVM: **81,74 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **No Wi-Fi, No Limit:** Connects through 4G LTE networks, ideal for places where constant Wi-Fi is not available
- ✓ **360° All-Round Protection:** Provides 360° horizontal & 130° vertical viewing range, eliminating blind spots
- ✓ **Free AI Detection:** Smart AI identifies people, pets, and vehicles, sending instant notifications through the Tapo app
- ✓ **1080P Full HD:** Reveals sharp images and vivid details with 1920 x 1080 pixels
- ✓ **Starlight Color Night Vision:** Captures vibrant images in low light up to 20 meters away
- ✓ **IP66 Weatherproof:** Works well in rain, dust, and heat, offering excellent waterproof and dustproof performance for outdoor scenarios
- ✓ **Sound and Light Alarm:** Craft your own audio alarm to deter unwelcome intruders and tailor the intensity of the dual spotlights
- ✓ **Local and Cloud Storage:** Save all your important moments to a microSD card (up to 512GB) or subscribe to Tapo Care for cloud service
- ✓ **Dual Mode Flexibility with 4G or PoE:** Power your camera with a DC adapter or Ethernet cable featuring PoE technology



Aprašymas

Power 360° Security with 4G LTE

Outdoor Pan/Tilt 4G LTE Camera

No Wi-Fi, No Limits

Backed by TP-Link's 4G networking expertise, Tapo C501GW reliably connects through 4G LTE networks, ideal for locations like garages, vacation

homes, warehouses, and farms where constant Wi-Fi is unavailable. Simply plug in a 4G SIM card (not included) for an easy, hassle-free internet setup.

360° All-Round Protection

Track the motion with 360° horizontal & 130° vertical viewing range, or turn on the patrol mode to keep the camera cruising among multiple customized points.

Multiple AI Detection for All Scenarios

Smart AI identifies people, pets, and vehicles and detects tampering and line crossing. It sends alerts only when necessary, ensuring you receive precise notifications about events as they occur.

Dual Mode Flexibility with 4G or PoE

Option 1: Power your camera with a DC adapter and connect internet with 4G SIM card.

Option 2: Power your camera with Ethernet cable featuring PoE technology for safe power and stable internet, bypassing complex wiring and electrician calls.

Designed to Resist Harsh Weather

With IP66 weatherproofing, Tapo C501GW offers excellent waterproof and dustproof performance for outdoor scenarios. It works well in rain, dust, and heat, operating reliably in different environments.

Sound and Light Alarm

Deter unwelcomed intruders with customizable audio and tailor the intensity of the dual spotlights for fine-tuned illumination.

24/7 Secure Local Recording & Cloud Storage

Save all your important moments to a microSD card1 (up to 512 GB) or subscribe to Tapo Care2 for cloud service after a free trial.

Flexible Antenna Placement

Install antennas with larger power according to your needs. The SMA connector is compatible with different antennas.

Customizable Activity Zone

Customize detection zones to receive alerts for your most important areas.

Two-Way Audio

Communicate directly with a subject in frame from wherever you are.

Voice Activated View

Works with Amazon Alexa and Google Home for hands-free automation.

Techninė specifikacija

Specifikations

Sandėlio grupė Surveillance Systems [+315][-2956]

Performance

Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wireless
Auto pan mode	Yes

Maximum operating distance	20 m
Day/night mode	Yes
Remote viewing	Yes
Built-in light	Yes
Antenna type	External
Antennas quantity	1
Design	
Mounting type	Wall
Product colour	White
Form factor	Turret
Housing material	Metal
Protection features	Waterproof
International Protection (IP) code	IP66
Weatherproof	Yes
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Lens viewing angle, horizontal	105°
Lens viewing angle, vertical	59°
Lens viewing angle, diagonal	122°
Tilt angle range	60 - 130°
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Panoramic camera	
Sensor type (panoramic camera)	CMOS
Lens system	
Recognize distance	20 m
Focal length range	3.17 mm
Fixed focus	Yes
Maximum aperture number	1.65
Fixed focal length	3.17 mm
Night vision	
Night vision	Yes

B/W night vision distance	29.9 m
LED type	IR/White
Infra-red wavelength	850 nm
Video	
Maximum resolution	1920 x 1080 pixels
Video compression formats	H.264
Supported graphics resolutions	1920 x 1080 (HD 1080)
Video recording	Yes
Frame rate	30 fps
Audio	
Built-in speaker(s)	Yes
Audio system	2-way
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	RTSP
Built-in microphone	Yes
Number of microphones	1
Audio detection	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.3af, IEEE 802.3at
SIM card slot	Yes
SIM card type	NanoSIM
Mobile network connection	Yes
Mobile network generation	4G
4G standard	LTE
Live view	Yes
Storage	
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1

DC-in jack	Yes
Security	
Built-in siren	Yes
Siren noise level	99 dB
Video motion detection	Yes
Alert notification type	Push notification, Snapshot alert message
Motion sensor	Yes
Mirror	Yes
Management features	
Cloud-managed	Yes
Reset button	Yes
Remotely operated	Yes
Power	
Power source type	AC, DC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
DC output voltage	12
DC output current	1 A
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	0 - 90%
Weight & dimensions	
Width	130.8 mm
Depth	84 mm
Height	116.1 mm
Width (with stand)	139.8 mm
Depth (with stand)	102.3 mm
Height (with stand)	234.2 mm
Packaging data	
Package width	160 mm
Package depth	210 mm

Package height	145 mm
Package weight	830 g
Package type	Box
Packaging content	
Number of cameras	1
Mounting kit	Yes
Mounting brackets included	Yes
Screws included	Yes
Drilling template included	Yes
Manual	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 13,00cm × 8,00cm
Svoris	1,50kg