

TP-Link Omada ES216G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black

Gamintojas: **TP-LINK** · Modelis: **ES216G** · EAN: **1210002600682** · Prekės kodas: **717738**



91,90 €

Kaina su PVM

Be PVM: **75,95 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 16× 10/100/1000Mbps RJ45 ports
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app
- ✓ VLAN, Port Isolation, Cable Test, QoS for reliable surveillance networking
- ✓ Automatic Loop Prevention and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/rack mounting design



Aprašymas

Omada Cloud Essentials — A Free and Easy Cloud-Based Network Management

Omada Cloud Essentials is a free, easy-to-use version of the Omada Cloud-based Controller. It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

Techninė specifikacija

Specifications

Sandėlio grupė	Networking [+782][-3085]
----------------	--------------------------

Management features

Switch type	Managed
-------------	---------

Switch layer	L2
--------------	----

Quality of Service (QoS) support	Yes
----------------------------------	-----

Web-based management	Yes
----------------------	-----

Cloud-managed	Yes
---------------	-----

Unified static configuration	Yes
------------------------------	-----

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	16
---	----

Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
---	--------------------------------

Gigabit Ethernet (copper) ports quantity	16
--	----

Power connector	AC-in jack
-----------------	------------

Network

Networking standards	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3i, IEEE 802.3x
----------------------	--

10G support	No
-------------	----

Zero Touch Provisioning (ZTP)	Yes
-------------------------------	-----

Port mirroring	Yes
----------------	-----

Flow control support	Yes
----------------------	-----

Link aggregation	Yes
------------------	-----

Auto MDI/MDI-X	Yes
----------------	-----

Auto-negotiation	Yes
------------------	-----

Fast leave	Yes
------------	-----

VLAN support	Yes
--------------	-----

Virtual LAN features	MTU VLAN, Port-based VLAN, Tagged VLAN
----------------------	--

Number of VLANs	32
-----------------	----

Data transmission

MAC address table	8000 entries
-------------------	--------------

Switching capacity	32 Gbit/s
--------------------	-----------

Forwarding rate	23.8 Mpps
-----------------	-----------

Store-and-forward	Yes
-------------------	-----

Jumbo frames support	Yes
----------------------	-----

Jumbo frames	15000
--------------	-------

Packet buffer memory	4 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Queue scheduling algorithms	Weighted Round Robin (WRR)
Design	
Rack mounting	Yes
Product colour	Black
LED indicators	Yes
Performance	
Flash memory	64 MB
Firmware upgradeable	Yes
Fanless	Yes
Mean time between failures (MTBF)	2131140 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	8.4 W
Surge protection	Yes
Surge protection voltage	6 kV
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	28.52 BTU/h
Weight & dimensions	
Width	294 mm
Depth	140 mm

Height	44 mm
--------	-------

Packaging content

Cables included	AC
-----------------	----

User guide	Yes
------------	-----

Rack mount kit	Yes
----------------	-----

Packaging data

Package type	Box
--------------	-----

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
-------------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	24,00cm × 35,00cm × 8,00cm
----------------------	----------------------------

Svoris	2,20kg
--------	--------