

DELL PowerEdge T360 server 480 GB Tower (4.5U) Intel Xeon 6 6315P 2.8 GHz 16 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **V3J7K** · EAN: **5397184969670** · Prekės kodas: **717766**



3 694,90 €

Kaina su PVM

Be PVM: **3 053,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6315P (12MB Cache, 2.8GHz)
- ✓ 16GB DDR5-SDRAM (1 x 16) & 480GB SSD
- ✓ iDRAC9, Enterprise 16G



Aprašymas

Processing performance, GPU support

The 4.5U, single-socket PowerEdge T360 is a specially designed form factor for customers desiring versatility, affordability, and processing power.

Techninė specifikacija

Specifications

Sandėlio grupė

Computers [+193][-2216]

Processor

Processor family

Intel Xeon 6

Processor manufacturer	Intel
Processor model	6315P
Processor frequency	2.8 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	4
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz
Memory	
Internal memory	16 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	Yes
Memory layout (slots x size)	1 x 16 GB
Memory data transfer rate	5600 MT/s
Storage	
Total storage capacity	480 GB
RAID support	No
Optical drive type	No
SSD capacity	480 GB
SSD interface	SATA III
SSD size	2.5"
Supported SSD sizes	3.5"
Number of SSDs supported	8
Supported RAID controllers	PERC H355 Adapter FH
Hot-Plug support	Yes
Drive writes per day (DWPD)	1
Storage drive adapter included	Yes

Storage drive adapter type	2.5" - 3.5"
Network	
LAN controller	Broadcom 5720
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Power cables quantity	2
Expansion slots	
PCI Express x4 slots	2
Design	
Chassis type	Tower (4.5U)
Product colour	Black
Bezel	Yes
Performance	
Remote administration	iDRAC9, Enterprise 16G
Software	
Operating system installed	No
Compatible operating systems	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Power	
Redundant power supply (RPS) support	No
Power supply	700 W
Number of main power supplies	1
Power supply input voltage	200 - 240 V
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 2048 m

Non-operating altitude	0 - 12000 m
Certificates	
80 PLUS certification	80 PLUS Titanium
Carbon footprint	
Total carbon footprint (kg of CO2e)	1409
Total carbon emissions, standard deviation (kg of CO2e)	1213
Carbon emissions, manufacturing (kg of CO2e)	295.89
Carbon emissions, logistics (kg of CO2e)	154.99
Carbon emissions, energy usage (kg of CO2e)	929.94
Carbon emissions, end-of-life (kg of CO2e)	28.18
PAIA version	1.4.0, 2024
Weight & dimensions	
Width	175 mm
Depth	581.1 mm
Packaging content	
Packaging content	European Power Cord 220V
Other features	
Data transfer rate	6 Gbit/s
Bytes per sector	512e
Target workload	Read Intensive (RI)
Matmenys ir svoris	
Matmenys (l × P × A)	55,00cm × 80,00cm × 37,00cm
Svoris	23,30kg