

DELL PowerEdge R260 server 2.4 TB Rack (1U) Intel Xeon 6 6315P 2.8 GHz 16 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **58K1M** · EAN: **5397184969717** · Prekės kodas: **717769**



4 322,89 €

Kaina su PVM

Be PVM: **3 572,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6315P (12MB Cache, 2.8GHz)
- ✓ 16GB DDR5-SDRAM (1 x 16) & 2400GB HDD
- ✓ iDRAC9, Enterprise 16G



Aprašymas

The 1U, single-socket Dell PowerEdge R260 is a short-depth form factor for customers desiring flexibility, affordability and processing power.

Techninė specifikacija

Specifications

Sandėlio grupė Computers [+193][-2216]

Processor

Processor family Intel Xeon 6

Processor manufacturer Intel

Processor model	6315P
Processor frequency	2.8 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
System bus rate	16 GT/s
Processor threads	4
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz

Memory

Internal memory	16 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	Yes
Memory layout (slots x size)	1 x 16 GB
Memory data transfer rate	5600 MT/s

Storage

Total storage capacity	2.4 TB
RAID support	No
Optical drive type	No
Number of HDDs installed	2
HDD capacity	1.2 TB
HDD interface	Serial Attached SCSI (SAS)
HDD speed	10000 RPM
HDD size	2.5"
Number of HDDs supported	6
Supported HDD sizes	2.5"
Supported RAID controllers	PERC H355 Adapter LP
Hot-Plug support	Yes

Network

LAN controller	Broadcom 5720
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Design	
Chassis type	Rack (1U)
Product colour	Black
Bezel	Yes
Performance	
Remote administration	iDRAC9, Enterprise 16G
Trusted Platform Module (TPM)	Yes
Software	
Operating system installed	No
Compatible operating systems	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Power	
Redundant power supply (RPS) support	No
Power supply	700 W
Number of main power supplies	1
Power supply input voltage	200 - 240 V
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m
Certificates	
80 PLUS certification	80 PLUS Titanium
Carbon footprint	

Total carbon footprint (kg of CO2e)	950
Total carbon emissions, standard deviation (kg of CO2e)	711
Carbon emissions, manufacturing (kg of CO2e)	304
Carbon emissions, logistics (kg of CO2e)	95
Carbon emissions, energy usage (kg of CO2e)	541.5
Carbon emissions, end-of-life (kg of CO2e)	9.5
PAIA version	PAIA 1.3.2, 2024
Weight & dimensions	
Width	482 mm
Height	42.8 mm
Packaging content	
Packaging content	Riser Config 1, Gen4 Riser European Power Cord 220V
Other features	
Data transfer rate	12 Gbit/s
Bytes per sector	512n
Matmenys ir svoris	
Matmenys (l × p × a)	60,00cm × 78,00cm × 25,00cm
Svoris	28,00kg